



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-824R1** - 4 Foot; Vapor Proof Linear Fixture with Integrated Microwave Sensor; CCT & Wattage Selectable; IP65 and IKo8 Rated; 120V-347V

- Wattage Selectable
- CCT Selectable
- Has Driver



### ELECTRICAL

Technology:	LED
Watts:	40W/50W/60W
Volts:	120V-347V
Lumens:	5360L-7991L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V; Integrated Sensor
Incandescent Equivalent :	300W-400W
HID Equivalent :	125W-150W
Operating Temperature :	-40C (-40F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Surge Protection :	Built-in surge protection - 2KV
THD:	17.60%
Power Factor :	>0.96
Warranty:	5 Year Limited - Fixtures

### PACKAGING

Each UPC:	045923650994
Each Quantity:	1
Each Dimensions:	49.61 x 5.71 x 3.94
Case UPC:	10045923650991
Case Quantity:	6
Case Dimensions:	49.61 x 11.42 x 11.81

### PHYSICAL

Finish:	Gray
Lens Material:	Polycarbonate (PC)
Finish Family:	Gray
Dimensions:	L:47.24" W:4.92" H:3.46"
Weight (Lbs.):	5.29
Material:	Plastic
Sensor:	Integrated Microwave Sensor

### COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-PGBKE7
DLC Primary Use:	Direct Linear Ambient Luminaires
CA Prop 65:	Lead
Vapor Tight Fixture Rated:	Yes
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IKo8
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions