

Project/Job Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_  
 Notes: \_\_\_\_\_



**65-865-4** - LED Area Light Type IV; 200W; Bronze Finish; 5000K; 277-480V



### ELECTRICAL

Technology:	LED
Watts:	200W
Volts:	277V-480V
Lumens:	26536L
Lamp Base :	Integrated
CRI:	80
CCT (Kelvins):	5000K
Color Description:	Natural Light
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
DimmableText:	0-10V Dimming
HID Equivalent :	400W
Operating Temperature :	-40C (-40F) to +45C (+113F)
Lamp Included :	Integrated
Number of LEDs :	294
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	>0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

### PACKAGING

Each UPC:	045923686542
Each Quantity:	1
Each Dimensions:	32.76 x 14.37 x 5.71
Case UPC:	10045923686549
Case Quantity:	1
Case Dimensions:	32.76 x 14.37 x 5.71

### PHYSICAL

Finish:	Bronze
Lens Material:	Polycarbonate (PC)
Finish Family:	Bronze
Dimensions:	L:30.28" W:12.39" H:3.11"
Weight (Lbs.):	8.42
Material:	Die-cast Aluminum
Sensor:	Optional

### COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-WDPAUR
DLC Primary Use:	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK10
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
B.U.G Rating:	B4-U3-G4
Restrictions:	No Restrictions

### INFO

Additional Info:	Powder Coated
Specification Note:	Type IV Light Distribution
Includes:	2-3/8 inch Slip-fitter Mount

**ACCESSORIES**

---



**65-870** Area Light; Universal; Direct and Slip Fitter Mount; Bronze Finish

---



**65-871** Area Light; Direct Mount; Square or Round; Pole Mount; Bronze Finish

---



**65-872** Area Light; Trunnion Mount; Bronze Finish

---



**65-873** Yoke Mount Bracket; Bronze Finish; For Use With 100W/150W/200W Area Lights; Bronze Finish

---



**65-875** Area Light Extended Slipfitter Mount with Sensor Knockouts; Bronze Finish

---



**65-876** Area Light Fixed Arm Mount with Sensor Knockouts; Bronze Finish

---



**65-878** Area Light Cutoff Shield; Bronze Finish; Only for 200W Fixture

---



**86-223** Area Light Photocell Socket; 277-480 Volt

---



**86-225** 10KV Area Light Surge Protector; 277-480 Volt

---



**86-226** 12-24 Volt Area Light PIR Sensor; 277-480 Volt

---