SATCO" NUVO"

Project Name

Location

Prepared By



NUVO	65-538
LED 50W LARGE	FLOOD LIGHT

Notes

GeneralStatusActiveFixture TypeFlood LightFinishBronzeWattage50Lumen Output5778CCT (Kelvin)4000TemperatureCool WhiteIP RatingIP65SpecificationsCRITechnologyLEDCRI80+Voltage100/-277VBeam Angle130Rated Hours50000Operating Temperature-20C (4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62Dimensions2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingSafety ListingCULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRodditional Information1/2" Thread knuckle mount		
Fixture TypeFlood LightFinishBronzeWattage50Lumen Output5778CCT (Kelvin)4000TemperatureCool WhiteIP RatingIP65SpecificationsSpecificationsTechnologyLEDCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (-4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62Dimensions10.19Compliance2.09Safety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	General	
FinishBronzeWattage50Lumen Output5778CCT (Kelvin)4000TemperatureCool WhiteIP RatingIP65SpecificationsTechnologyCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62Dimensions	Status	Active
Wattage50Lumen Output5778CCT (Kelvin)4000TemperatureCool WhiteIP RatingIP65SpecificationsTechnologyLEDCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (-4F) to a maximum of +45C (-113F)DimmableNon-DimmableWeight (lb.)3.62Dimensions-209Width (in.)8.5Length (in.)10.19ComplianceCULusSafety ListingcULusLocation RatingWetUL ApplicationYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Fixture Type	Flood Light
Lumen Output5778CCT (Kelvin)4000TemperatureCool WhiteIP RatingIP65SpecificationsTechnologyLEDCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Finish	Bronze
CCT (Kelvin)4000TemperatureCool WhiteIP RatingIP65SpecificationsIP65TechnologyLEDCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature20C (-4F) to a maximum of +45C (-113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsIP1000000000000000000000000000000000000	Wattage	50
TemperatureCool WhiteIP RatingIP65SpecificationsIP65TechnologyLEDCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62Dimensions2.09Width (in.)2.09Width (in.)10.19ComplianceSafety ListingSafety ListingcULusLocation RatingWetUL ApplicationYesDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Lumen Output	5778
IP RatingIP65SpecificationsTechnologyLEDCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationYesDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	CCT (Kelvin)	4000
SpecificationsTechnologyLEDCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (-4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Temperature	Cool White
TechnologyLEDCRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (-4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	IP Rating	IP65
CRI80+CRI80+Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (-4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62Dimensions-209Width (in.)2.09Width (in.)8.5Length (in.)10.19Compliance	Specifications	
Voltage100V-277VBeam Angle130Rated Hours50000Operating Temperature-20C (-4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Technology	LED
Beam Angle130Beam Angle130Rated Hours50000Operating Temperature-20C (-4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	CRI	80+
Rated Hours50000Operating Temperature-20C (-4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Voltage	100V-277V
Operating Temperature-20C (-4F) to a maximum of +45C (+113F)DimmableNon-DimmableWeight (lb.)3.62DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Beam Angle	130
Operating Temperature(+113F)DimmableNon-DimmableWeight (lb.)3.62Dimensions2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Rated Hours	50000
Weight (lb.)3.62Dimensions2.09Height (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceCullusSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Operating Temperature	
DimensionsHeight (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Dimmable	Non-Dimmable
Height (in.)2.09Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Weight (lb.)	3.62
Width (in.)8.5Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Dimensions	
Length (in.)10.19ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Height (in.)	2.09
ComplianceSafety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional InformationAdditional Information1/2" Thread knuckle mount	Width (in.)	8.5
Safety ListingcULusLocation RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Length (in.)	10.19
Location RatingWetUL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Compliance	
UL ApplicationWallEnergy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Safety Listing	cULus
Energy StarNoDLC ApprovedYesDLC IDPLTS9UONEDIXCEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	Location Rating	Wet
DLC Approved Yes DLC ID PLTS9UONEDIX CEC Status California T24 Compliant CA Prop 65 Lead RoHS Compliant Yes Additional Information 1/2" Thread knuckle mount	UL Application	Wall
DLC ID PLTS9UONEDIX CEC Status California T24 Compliant CA Prop 65 Lead RoHS Compliant Yes Additional Information 1/2" Thread knuckle mount	Energy Star	No
CEC StatusCalifornia T24 CompliantCA Prop 65LeadRoHS CompliantYesAdditional Information1/2" Thread knuckle mount	DLC Approved	Yes
CA Prop 65 Lead RoHS Compliant Yes Additional Information 1/2" Thread knuckle mount	DLC ID	PLTS9UONEDIX
RoHS Compliant Yes Additional Information 1/2" Thread knuckle mount	CEC Status	California T24 Compliant
Additional Information Additional Information 1/2" Thread knuckle mount	CA Prop 65	Lead
Additional Information 1/2" Thread knuckle mount	RoHS Compliant	Yes
	Additional Information	
	Additional Information	1/2" Thread knuckle mount
Warranty 5 Year Limited	Warranty	5 Year Limited

For More Information Visit: <u>https://www.satco.com/</u>

