

CHAMELEON Wall Sconce

oxygen

120v : **3-521-xx**

277v : **37-521-xx**

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-40 Aged Brass



-14 Polished Chrome




-22 Oiled Bronze



-24 Satin Nickel

- LIGHT SOURCE** 1 x 8.2W LED, 3000K, CRI 90
- LUMINAIRE POWER** 10.4W at 120V
- RATED LIFE** 60000 hr RL
- OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: 832 lm (LM-79)
- INPUT VOLTAGE** 120V or 277V
- DRIVER OUTPUT** 350mA, 12W
- DIMMING** 0-10v &Phase (ELV) Dimming
50/60Hz 100% to 10% Dimming
- CONSTRUCTION** Plated Steel and Acrylic
- DIFFUSER** - Matte White Acrylic
- FINISHES** Polished Chrome (-14), Oiled Bronze (-22), Satin Nickel (-24),
Aged Brass (-40)
- MOUNTING** 4" Octagonal J-Box
- STANDARDS** ETL Dry/Damp listed, ADA compliant, Conforms to UL STD
1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

- W:** 11.44"
- H:** 10.94"
- Ext:** 4.00"
- M.C:** 5.25" From top of fixture

Order example for standard fixture:

3-514-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v, 37: 277v

Order example for optional color temperatures: **3-514-2724**

27: 2700K, 35: 3500K, 40: 4000K

