

Project:

Fixture Type:

Location

Contact:

Simple LED

Ceiling cord Mounted • Dry Location Listed PROGRESS LED



Description:

One-light cord-hung pendant with an LED source that is neatly tucked inside a frosted acrylic shade. A light commercial pendant ideal for restaurants, bar and hotel applications. Antique Bronze finish.

Specifications:

- White polystyrene Shade
- White acrylic Diffuser
- Light commercial LED pendant.
- Frosted acrylic shade.
- $\boldsymbol{\cdot}\,$ Ideal for restaurants, bar and hotel applications.
- Dimmable to 10% with many ELV dimmers
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5 in W., 1.0625 in depth
- Mounting strap for outlet box included
- + 120 in of wire supplied

Performance:


Number of Modules	1
Input Power	9 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	405/54 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30 °C
Warranty	5-year Limited Warranty
Labels	cCSAus Dry Location Listed
	ENERGY STAR [®] qualified



Dimensions:

Diameter: 5-7/8 in Height: 8-5/8 in Overall Ht. W/Cord: 130 in

White polystyrene Shade Width: 5-13/16 in





Simple LED

Ceiling cord Mounted • Dry Location Listed PROGRESS LED



P5176-2030K9 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron Nova T NTELV-300
Lutron Vierti VTELV-600
Lutron Ariadni AYCL-153P
Lutron Diva DVCL-153P
Lutron Maestro MAELV-600
Lutron spacer/system SPSELV-600
Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.



P5176-2030K9