

Z-1060 LED

Wall Mounted • Wet Location Listed **PROGRESS LED**

Description:

Z-1060 Collection One-Light LED Wall Lantern

Specifications:

- Etched Opal Glass Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" recessed outlet box: 4.5 in W., 4.5 in ht., 0.75 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied
- Dark Sky compliant

Performance:

Number of Modules	1
Input Power	9 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	624/66 (LM-82)
Lumens/LPW (Delivered)	236/25.7 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30°C
Warranty	5-year Limited Warranty
Labels	cCSAus Wet Location Listed Meets California Title 24 JA8-2016


P560072-031-30



Dimensions:

Width: 4-1/2 in
 Depth: 4-3/4 in
 Height: 4-1/2 in
 H/CTR: 2-1/4 in

Etched Opal Glass Diffuser
 Width: 3-1/2 in
 Height: 3-1/4 in




P560072-031-30

Photometrics:

ELECTRICAL DATA	P560072-031-30
Input Voltage	120 V
Input Frequency	60 Hz
Input Current	0.075 A
Power Factor	Greater than 0.90
THD	<20%
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Operating Temperature	-30 °C
Dimming	Yes*
Over-voltage, over-current, short-circuit protected	
*See Dimming Notes for more information	

P560072-031-30
 LED Light Engine: 3000 K 90 CRI
 System Wattage: 9
 Fixture delivered lumens: 236
 Fixture Efficacy: 25.7
 Spacing Criteria: 1.85



CANDELA DISTRIBUTION

DEG	CANDELA	LUMENS
0	22.5	
5	23.4	2
15	26.1	7
25	28.1	13
35	28.8	18
45	28.5	22
55	27.1	24
65	25.3	25
75	22.7	24
85	19.5	21
90	18.3	
95	17.3	19
105	15.6	17
115	13.7	14
125	10.9	10
135	7.8	6
145	4.8	3
155	1.9	1
165	0.7	0
175	0.1	0
180	0.1	

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%FIXT
0-30	23	10.0
0-40	41	17.9
0-60	87	38.3
0-90	157	69.4
90-120	49	21.7
90-130	59	25.9
90-150	68	30.1
90-180	69	30.6
0-180	227	100.0

Test 17.01615 Test Date 06/07/17

P560072-031-30

Dimming Notes:

P560072-031-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Diva DVELV-300P

Lutron_Nova T NTELV-300

Lutron_Caseta

Lutron_Ariadni AY-600P

Leviton_Illumatech IPI06-1LZ

Leviton_SureSlide 6672

Lutron_Skylark Contour CTCL-153P

Lutron_Diva DVCL-153P

Lutron_Toggler TGCL-153P

Lutron_Maestro MACL-153M

Lutron_Ariadni AYLV-600P

Lutron_Nova T NTLV-600

Lutron_Maestro MAELV-600

Lutron_spacer/system SPSELV-600

Leviton_Renoir II AWRMG-EAW

Lutron_Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.