

# One-Light Outdoor

Project:

Fixture Type: Location:

Contact:

Wall mounted • Wet location listed PROGRESS LED



## P5864-3130K9

Westport LED offers traditional styling to complement a variety of home decor options. A durable diecast aluminum frame cradles a softly diffused seeded glass shade. 3000K, 90+ CRI 1,211 lumens 71.2 lumens/watt per module (source). One-light LED wall mount.

#### **Specifications:**

**Description:** 

- Black (-31) (powder coat paint)
- Die-cast aluminum Construction
- Etched Seeded glass shade
- LED Module is replaceable (part # 93053641)
- Traditional styling.
- · Softly diffused seeded glass shade.
- $\cdot$  Complements many home decor styles with beaded detailing.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR<sup>®</sup> qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

### Performance:

Input Power       17w         Input Voltage       120 V         Input Frequency       60 Hz         Lumens/LPW (Source)       1211/71.2 (LM-82)         Lumens/LPW (Delivered)       594/38.0769230769231 (LM-79)         CCT       3000 K         CRI       90 CRI         Life (hours)       60,000 (L70/TM-21)         FCC       Meets FCC Title 47, Part 15 Class B         Min. Start Temp       -30 °C         Max. Operating Temp       5 year warranty			
Input Voltage 120 V Input Frequency 60 Hz Lumens/LPW (Source) 1211/71.2 (LM-82) Lumens/LPW (Delivered) 594/38.0769230769231 (LM-79) CCT 3000 K CCT 3000 K CCT 60,000 (L70/TM-21) FCC 164 Sec FCC Title 47, Part 15 Class B Min. Start Temp 30 °C Max. Operating Temp 30 °C Maranty 5 year warranty Labels CCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Number of Modules	1	
Input Frequency60 HzLumens/LPW (Source)1211/71.2 (LM-82)Lumens/LPW (Delivered)594/38.0769230769231 (LM-79)CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelsCCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Input Power	17w	
Lumens/LPW (Source) 1211/71.2 (LM-82) Lumens/LPW (Delivered) 594/38.0769230769231 (LM-79) CCT 3000 K CRI 90 CRI Life (hours) 60,000 (L70/TM-21) FCC Meets FCC Title 47, Part 15 Class B Min. Start Temp -30 °C Max. Operating Temp 30 °C Max. Operating Temp 5 year warranty Labels CCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Input Voltage	120 V	
Lumens/LPW (Delivered)594/38.0769230769231 (LM-79)CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelsCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Input Frequency	60 Hz	
CCT3000 KCRI90 CRILife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelsCCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Lumens/LPW (Source)	1211/71.2 (LM-82)	
CRIDisplay timeLife (hours)60,000 (L70/TM-21)FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarrantyLabelsCCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Lumens/LPW (Delivered)	594/38.0769230769231 (LM-79)	
Life (hours) 60,000 (L70/TM-21) FCC Meets FCC Title 47, Part 15 Class B -30 °C Max. Operating Temp 30 °C Warranty 5 year warranty Labels cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	ССТ	3000 K	
FCCMeets FCC Title 47, Part 15 Class BMin. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	CRI	90 CRI	
Min. Start Temp-30 °CMax. Operating Temp30 °CWarranty5 year warrantyLabelscCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Life (hours)	60,000 (L70/TM-21)	
Max. Operating Temp 30 °C Warranty 5 year warranty Labels cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	FCC	Meets FCC Title 47, Part 15 Class B	
Warranty 5 year warranty Labels cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Min. Start Temp	-30 °C	
Labels cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Max. Operating Temp	30 °C	
ENERGY STAR® qualified Meets California Title 24 high efficacy requirements	Warranty	5 year warranty	
Meets California Title 24 high efficacy requirements	Labels	cCSAus Wet location listed	
		ENERGY STAR <sup>®</sup> qualified	
for outdoor use only		Meets California Title 24 high efficacy requirements	
		for outdoor use only	

### Images:



#### **Dimensions:**

Width: 11" Depth: 12-7/8" Height: 15-3/8" H/CTR: 4"



# One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED



# P5864-3130K9

#### **Dimming Notes:**

P5864 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.