

Project:

Fixture Type:

Location:

Contact:

LED Shaded Sconce

Wall Mounted • Damp Location Listed PROGRESS LED



Description:

This wall sconce is ideal for corridor and hotel lighting. Circular forms created a stunning brushed nickel frame. The light fixture is topped by a summer linen shade that creates a calming glow sure to welcome tired travelers.

Specifications:

- Summer Linen fabric Shade
- $\boldsymbol{\cdot}\,$ This wall sconce is ideal for corridor and hotel lighting.
- $\cdot\,$ Circular forms created a stunning brushed nickel frame.
- The light fixture is topped by a summer linen shade that creates a calming glow sure to welcome tired travelers.
- $\boldsymbol{\cdot}$ Ideal for any hallway, foyer, living room, sitting room, or bedroom.
- Perfect for mid-century modern, transitional, modern, or contemporary settings.
- Measures 14-inch width by 21-1/4-inch height.
- Uses one LED module (9w max).
- Compatible with many Triac/ELV dimmers (see dimming controls)
- Includes installation instructions and mounting hardware.
- · Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- Dimmable to 10% brightness (See Dimming Notes)
- · Canopy covers a standard 4" recessed outlet box: 8 in W., 6.5 in ht., 0.812 in depth
- Mounting plate for outlet box included
- 6 in of wire supplied
- · Americans With Disabilities Act (ADA) compliant

Performance:

| Number of Modules | 1 |
|---------------------|------------------------------------|
| Input Power | 9 W |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 624/66 (LM-82) |
| ССТ | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 60000 (L70/TM-21) |
| EMI/RFI | FCC Title 47, Part 15, Class B |
| Warranty | 5-year Limited Warranty |
| Labels | cCSAus Damp Location Listed |
| | ENERGY STAR [®] qualified |
| | Meets California Title 24 JA8-2016 |


P710058-009-30



Dimensions:

Width: 14 in Height: 21-1/4 in Depth: 3-7/8 in H/CTR: 3-1/4 in

Summer Linen fabric Shade Width: 16-7/8 in Height: 7-5/16 in





LED Shaded Sconce

Wall Mounted • Damp Location Listed PROGRESS LED



P710058-009-30 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

| Lutron Diva DVELV-300P | |
|----------------------------------|--|
| Lutron Nova T NTELV-300 | |
| Lutron Caseta | |
| Lutron Ariadni AY-600P | |
| Leviton Illumatech IPI06-1LZ | |
| Leviton SureSlide 6672 | |
| Lutron Ariadni AYCL-153P | |
| Lutron Skylark Contour CTCL-153P | |
| Lutron Diva DVCL-153P | |
| Lutron Toggler TGCL-153P | |
| Lutron Maestro MACL-153M | |
| Lutron Ariadni AYLV-600P | |
| Lutron NOVA T NTLV-600 | |
| lutron Maestro MAELV-600 | |
| Lutron spacer/system SPSELV-600 | |
| Lutron Renoir II AWRMG-EAW | |
| Lutron Nova N-600 | |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P710058-009-30