PROGRESS LIGHTING[™]

Project:

Fixture Type:

Location:

Contact:

P710073-009 Lassiter

Manifest a swoon-worthy lighting experience with the stunning blend of modern and traditional styles in this one-of-a-kind wall bracket. Square tubing with clean, sharp angles demand your attention and appreciation. A beautiful brushed nickel finish coats a handsome rectangular backplate. A striking vintage light socket boasts its bold yet simple demeanor within the safety of a sophisticated clear glass shade.

- A striking vintage light socket boasts its bold yet simple demeanor within the safety of a sophisticated clear glass shade.
- A beautiful brushed nickel finish coats a handsome rectangular backplate.
- Square tubing with clean, sharp angles demand your attention and appreciation.
- Ideal for any bedroom, sitting room, living room, bathroom, hallway, or foyer.
- Perfect for modern, new traditional, or contemporary settings.
- Measures 4-7/8-inch width by 19-1/4-inch height.
- Uses one medium base bulb that is sold separately (60w max LED or incandescent).
- Able to be fully dimmable with dimmable bulbs.

Glass/Shade: Clear glass Cylindrical Shade

Category: Wall Brackets Finish: Brushed Nickel (Plated) Construction: Steel Construction

- Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.



Width: 4-7/8 in Height: 19-1/4 in Depth: 6-1/2 in H/CTR: 9-3/8 in (glass facing up)

Clear glass Cylindrical Shade Width: 4 in Height: 7 in

| MOUNTING | ELECTRICAL | LAMPING | ADDITIONAL INFORMATION |
|--|---------------------------|---|----------------------------|
| Wall mounted | Prewired | Quantity: One 60 W max. Medium Base or | CULus Damp Location Listed |
| Mounting plate for outlet box included | 6 inches of wire supplied | LED equivalent | 1-year Limited Warranty |
| | 120 V | E26 base Porcelain socket | |
| Fixture can be installed with glass facing up or down | | | |

Canopy covers a standard 4" recessed outlet box: 5" W., 8" ht., 0.875" depth