

IMPORTANT SAFETY INSTRUCTIONS:

- * This lamp has a polarized plug (one blade is wider than the other) as a feature to reduce the risk of electric shock. This plug will fit in a polarized outlet only one way. If it does not fit fully in the outlet, reverse the plug. If it still does not fit, contact a qualified electrician. Do NOT alter the plug.
- * Do not use with an extension cord unless the plug from the lamp can be fully inserted into the extension cord receptical.
- * Switch power off and remove plug from the wall outlet before replacing the bulb.
- * Do not connect electricity until lamp is fully assembled.
- * This lamp is UL rated for dry locations.

ASSEMBLY INSTRUCTIONS:

NOTE: Do not connect electricity until lamp is fully assembled.

- 1. Unpack all parts and remove packing materials.
- 2. Remove finial (A) from shade riser (D). Thread shade riser (D) onto socket housing (E).
- 3. Place shade (C) onto shade riser (D). Place shade lock (B) onto shade riser (D). Note: shade lock (B) should be turned so cutouts fit over alignment arms located at the top of shade riser (D).
- 4. Thread finial (A) back onto shade riser (D) to secure placement of shade.
- 5. Insert (2) 100W Max. Type A, medium base bulbs into the sockets.
- 6. Insert polarized plug (G) into wall outlet.
- 7. Control power to lamp by operating full range dimmer (F).
- ** To clean, use a soft cloth only. Do not use any chemical or abrasive cleaners. **