



Project/Job Name: _____
 Location: _____
 Fixture Type: _____
 Notes: _____

S11628R1 - 12 Watt LED Direct Wire Downlight; Gimbaled; 3.5 Inch; CCT Selectable; Square; Remote Driver; Black Finish; 840 Lumens; 120 Volt

- Air Tight
- IC Rated
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	12W
Volts:	120V
Lumens:	840L
CRI:	90
Rg Value :	51
CCT (Kelvins):	2700K/3000K/3500K/4000K/5000K
Beam Spread :	40
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Number of LEDs :	12
Connection:	Direct Wired
THD:	<30%
Power Factor :	>0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923311314
Each Quantity:	1
Each Dimensions:	5.31 x 3.74 x 5.31
Case UPC:	10045923311311
Case Quantity:	12
Case Dimensions:	12.20 x 11.42 x 11.61

INFO

Additional Info:	360 Degree Rotation; 30 Degree Tilt
------------------	-------------------------------------

PHYSICAL

Finish:	Black
Lens Finish:	Frost
Lens Material:	Poly methyl methacrylate (PMMA)
Finish Family:	Black
Dimensions:	L:4.38" W:4.38" H:2.10"
Weight (Lbs.):	1.01
Material:	Aluminum

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2684097
Energy Star Lamp Category:	Downlight Recessed
UL/ETL Standard:	ANSI/UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

ACCESSORIES

**80-973** Emergency Driver Enclosure; For use with S8000 and S8002**80-987** Emergency Remote Test Switch; Single Gang Plate; White Finish**S8000** 5 Watt LED Emergency Driver; 120-277 Volts**S8002** 10 Watt LED Emergency Driver; 120-277 Volt
