



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11878** - 11 Watt; 4"; Directional Low-Profile Downlight; CCT Selectable; 120 Volt; White Finish

• CCT Selectable

• IC Rated



## ELECTRICAL

Technology:	LED
Watts:	11W
Volts:	120V
Lumens:	700L
CRI:	90
CCT (Kelvins):	2700K/3000K/3500K/4000K/5000K
Beam Spread :	107
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Triac
Incandescent Equivalent :	50W
Operating Temperature :	-15C (+5F) to +40C (+104F)
Replaceable Light Source :	No
THD:	20%
Power Factor :	0.95
Warranty:	5 Year Limited - Fixtures

## PACKAGING

Each UPC:	045923118784
Each Quantity:	1
Each Dimensions:	5.59 x 3.98 x 5.71
Case UPC:	10045923118781
Case Quantity:	8
Case Dimensions:	11.97 x 8.62 x 12.40

## PHYSICAL

Finish:	White
Lens Material:	Polycarbonate (PC)
Finish Family:	White
Dimensions:	H:1.57" DIA:4.92"
Weight (Lbs.):	0.9
Material:	Aluminum

## INSTALLATION

Max Drywall Thickness:	1 in.
------------------------	-------

## COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2631725
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

**ACCESSORIES**

---

**80-943**New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.25-inch hole diameter

---

**80-946**4" Goof Ring for Remote Driver Installation

---

**80-950**New Construction Mounting Plate for Stud/Joist mounting of 4-inch Recessed Downlights; Up to 4.563-inch hole diameter

---

**80-973**Emergency Driver Enclosure; For use with S8000 and S8002

---

**80-985**6 FOOT REMOTE DRIVER 3-PIN EXT

---

**80-987**Emergency Remote Test Switch; Single Gang Plate; White Finish

---

**S8000**5 Watt LED Emergency Driver; 120-277 Volts

---

**S8002**10 Watt LED Emergency Driver; 120-277 Volt

---



**S11878** - 11 Watt; 4"; Directional Low-Profile Downlight; CCT Selectable; 120 Volt; White Finish

**DIMMER COMPATIBILITY**

---

Leviton	6672
Leviton	6674
Leviton	66ELV
Satco	80/2699
Satco	80/2700
Satco	80/2701
Satco	80/2702
Satco	80/2703
Satco	80/2704
Satco	86/103
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	AYCL-253P
Lutron	CTCL-153P
Lutron	CTRP-253P
Eaton	DALo6P-C2
Leviton	DDL06
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSEo6-10Z
Leviton	DSL06
Leviton	DSL06-1LZ
Leviton	DSM10

Eaton DULo6P-C2

Lutron	DVCL-153P
Lutron	DVCL-253P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	DZ6HD
Lutron	HQR-3LD
Lutron	HQR-3PD
Lutron	HQRA-PRO
Lutron	HQRD-10D
Lutron	HQRD-10NBD
Lutron	HQRD-6ND
Lutron	HQRD-HN6BRL
Lutron	HQRD-PRO
Lutron	HRST-PRO-N
Leviton	IPE04-1L
Leviton	IPL06
Lutron	LECL-153P
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MACL-LFQ
Precision	MR42400PLS
Lutron	MRF2-3LD
Lutron	MRF2-3PD
Lutron	MRF2S-6ELV
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Hubbell	NXFRD-UNV

<b>Overdrive</b>	ODMR0205
<b>Lutron</b>	PD-10NXD
<b>Lutron</b>	PD-3PCL
<b>Lutron</b>	PD-5NE
<b>Lutron</b>	PD-6WCL
<b>Lutron</b>	PHPM-WBX-120
<b>Lutron</b>	RCL-153PNL
<b>Leviton</b>	RELo6-WW
<b>Eaton</b>	RF9640-ND
<b>Legrand</b>	RH703PTUTC
<b>Legrand</b>	RHCL450PTC
<b>Leviton</b>	RNLo6-10Z
<b>Lutron</b>	RRD-10D
<b>Lutron</b>	RRD-3PD
<b>Lutron</b>	RRD-6CL
<b>Lutron</b>	RRD-6ND
<b>Lutron</b>	RRD-H6BRL
<b>Lutron</b>	RRD-PRO
<b>Lutron</b>	RRST-PRO-N
<b>Satco</b>	S11268
<b>Satco</b>	S11270
<b>Eaton</b>	SALo6P
<b>Lutron</b>	SCL-153P
<b>Lutron</b>	ST-PRO-N
<b>Lutron</b>	STCL-153M
<b>Eaton</b>	SUF7
<b>Eaton</b>	TALo6P-C2
<b>Lutron</b>	TGCL-153PH

<b>Leviton</b>	TSL06
<b>Leviton</b>	TSM10
<b>Lutron</b>	TTCL-100H
<b>Eaton</b>	VSUL06D
<b>Acuity</b>	WSX-PDT-WH
<b>Legrand</b>	WWRL50WH