



Project/Job Name: _____
 Location: _____
 Fixture Type: _____
 Notes: _____

S16443 - 48 Watt T8 LED; CCT Selectable; 120-277 Volt; Single or Double Ended; Type B Ballast Bypass

- CCT Selectable
- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	48W
Volts:	120V-277V
Lumens:	6700L/6900L/6600L
CRI:	83
CCT (Kelvins):	4000K/5000K/6500K
Temperature:	Cool White to Daylight
Beam Spread :	360
Hours Rated:	50000
Dimmable:	Non-Dimmable
Fluorescent Equivalent :	135W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballast Bypass/Direct:	Ballast Bypass
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended, Double Ended
Number of LEDs :	768
THD:	25%
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - T8 LED Bulbs

PACKAGING

Each UPC:	045923164439
Each Quantity:	1
Each Dimensions:	120.00 x 1.15 x 1.15
Inner UPC:	20045923164433
Inner Quantity:	0
Inner Dimensions:	0.00 x 0.00 x 0.00
Case UPC:	10045923164436
Case Quantity:	10
Case Dimensions:	120.00 x 7.87 x 4.92

INFO

Tube Guard Use:	_____
-----------------	-------

PHYSICAL

ANSI Base:	R17d
Base:	Recessed Double Contact HO/VHO
Shape:	T8
Finish:	White
Lens Finish:	Frost
Lens Material:	Plastic
MOD (In.):	1.13
MOL (In.):	117.81
Nominal Length:	120.00
Weight (Lbs.):	1.96
Material:	Polycarbonate (PC)

COMPLIANCE

Safety Listing:	cULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	ETL Sanitation listed (conforms to NSF)
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions