SONNEMAN A WAY OF LIGHT

Project:

Torc LED Chandelier Spec Sheet

SKU: 3153.25 Learn more at: https://sonnemanlight.com/torc-led-chandelier

Description: The movement of offset arcs rotate in suspension to form a modern interplay of deconstruction. Also available as a single pendant.

Type #:



Dimensions

Height:	56"
Width:	24.5"
Length:	4.5"
Diameter:	24.75"
Canopy/Backplate/Base:	5"
Hanging Details:	6' Adjustable
	Cord
Size:	Triple
	Pendant
Canopy/Backplate/Base Height:	2

Yes

3

51

90

1

4800

3120 3000K

Driver

Canopy TRIAC/ELV/

0-10V

51

Integral LED

120-277VAC

Electrical Specs

Bulb(s) Included?: Bulb 1 Type: Bulb Quantity: Input Voltage: Wattage: Initial Lumens: Delivered Lumens: Color Temperature: CRI: Power Supply Type: Power Supply Quantity: Power Supply Location: Dimming Type:

Bulb Max Wattage:

Installation

Installation:

Sloped Ceiling Compatible?: Minimum Hanging Height: Maximum Hanging Height:

Shipping

Carton 1 L x W x H:	
Carton 1 Gross Weight:	

Shade

Shade 1 Material:

Optical Silicone

Licensed

required

58"

130"

electrician

Compatible

28" X 28" X 11"

10 LBS

Available Finishes

Available Finishes: Satin Black (.25), Satin White (.03)

General Listings

Features: Certification: Color/Finish:

Dark Sky Friendly:

Damp Rated C-ETL-US Satin Black (.25) N