

Project:

REALS LED Surface Mount Spec Sheet

SKU: 7309.XX.DL.98-WL Learn more at: https://sonnemanlight.com/reals-led-surface-mount

Description: REALS® surface-mounted lights are neatly compact and solidly built. They offer a range of lens variations within the tightly defined geometry of their die-cast rings. Also available as a Downlight Sconce, <a href="Up/Downstandiago-up/

Type #:



Dimensions

Height: 3.25"
Diameter: 5"
Canopy/Backplate/Base: 5"

Electrical Specs

Bulb(s) Included?:
Bulb 1 Type: Yes Integral LED **Bulb Quantity:** Input Voltage: 120VAC Wattage: 10 Initial Lumens: 1040 Color Temperature: 3000K 90 Power Supply Type: Driver Power Supply Quantity: Outlet Box Power Supply Location: Dimming Type: TRIAC/ELV Bulb Max Wattage: 10

Installation

Installation:

Shipping

Carton 1 L x W x H: 9" X 9" X 6"
Carton 1 Gross Weight: 3 LBS
Fixture Weight: 2

Licensed

electrician

required

Shade

Lens Type: Dome Lens
Shade 1 Material: Frosted
White
Polycarbonat

Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

General Listings

Features: Wet Rated
Certification: C-ETL-US
Color/Finish: Textured
White (.98)
Dark Sky Friendly: N