

# Filo 23 Outdoor Wall

7000WFLO\_23 | 1.1



### GENERAL PRODUCT INFORMATION:

This product is suitable for wet locations.

These fixtures are intended to be installed utilizing NEC compliant junction boxes.


This product can be dimmed with most ELV, TRIAC or 0-10V dimmers.

This instruction shows a typical installation.



**CAUTION - RISK OF FIRE**  
 This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.  
**Use minimum 90°C supply conductors.**


**SAVE THESE INSTRUCTIONS!**



TECH LIGHTING  
 7400 Linder Ave., Skokie, IL 60077  
 T 847.410.4400 | F 847.410.4500  
 www.techlighting.com

# Install the Fixture

1A



- 1 With the provided Allen wrench, remove the set screw from the bottom of the fixture base.
- 2 Remove the mounting plate from the fixture base
- 3 Install the mounting plate to the junction box with the two #8-32 screws provided and ensure the mounting plate is level.
- 4 Connect the fixture to a suitable ground in accordance with local electrical codes.
- 5 Connect the white wire to the neutral power line with a wire nut.
- 6 Connect the black wire to the hot power line with a wire nut.
- 7 Use the gray and purple dimming wires for 0-10v dimming application (if not in use, make sure to cap these wires off). **Warning:** The purple and gray wires are only used for 0-10v dimming. For all other applications, do not connect the gray and purple wires.
- 8 Properly place all wires and wire nut connections into the junction box, mount the fixture base onto the mounting plate, and secure it in place by reinstalling the set screw using the provided Allen wrench.
- 9 For wet locations, caulk around the base of the fixture with waterproof construction sealant.