

PRODUCT FEATURES

- Available in modern finishes
- Includes Louver Lens Holder
- MR16 holds up to two lenses or louvers. MR11 (solid only) can hold up to two lenses or louvers



LAMPING

Includes Louver Lens Holder. MR16 holds up to two lenses or louvers. Available for use on , Helios, Roto, mo-pivot, k-pivot, k-jane, mo wally. (sold seperately)

Backlight Shield

ORDERING INFORMATION

700MR	SHAPE OR SIZE	COLOR
	16M MR16 MESH	CH ALUMINIUM
	16S MR16 SOLID	BZ ANTIQUE BRONZE
		BK BLACK

700MR _____

JOB NAME _____


NOTES _____



BACKLIGHT SHIELD

SPECIFICATIONS

PRIMARY MATERIAL	
SHADE MATERIAL	
NET WEIGHT	0.05 lbs
HEIGHT	1.3in
WIDTH	2.3in
LENGTH	2.3in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE/ DIMMING TYPE				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

* Dimming information available at www.techlighting.com/Downloads#dimming
 ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

