

COLLIER ALABASTER 84 CHANDELIER

VISUAL COMFORT & Co.

PRODUCT FEATURES



LAMPING

Includes 28.7 watt, 1582 total delivered lumens, 90 CRI 2700K or 3000K LED modules. Remote dimmable with most LED compatible ELV and TRIAC dimmers. 277V dimmable with 0-10V dimmers. Surface dimmable with ELV and TRIAC dimmers. Remote 120V or 277V. Surface 120V-277V. Can be installed on a sloped ceiling up to 45°.

ORDERING INFORMATION

SLCH553	COLOR TEMP	COLOR	FINISH	LAMP
	27 2700K	ALB ALABASTER	BZ BRONZE	R REMOTE
	30 3000K		HAB HAND RUBBED ANTIQUE BRASS	R-277 REMOTE 277V
			N POLISHED NICKEL	S SURFACE

SLCH553 _____

JOB NAME _____

NOTES _____



SPECIFICATIONS

PRIMARY MATERIAL	Aluminum or Brass
SHADE MATERIAL	Alabaster
NET WEIGHT	25 lbs
HEIGHT	89.7in
WIDTH	2in
LENGTH	2in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
MIN. HANGING HEIGHT	89.7in
MAX HANGING HEIGHT	92.7in
TOTAL CORD LENGTH	
TOTAL STEM LENGTH	
STEM QTY	
SLOPED CEILING ADAPTABLE?	Yes 45° Max
GENERAL LISTING	ETL Listed
INCLUDES	

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		1582		
WATTS		28.7		
MAX WATTAGE PER BULB		28.7W		
		120V ELV, TRIAC 277V 0-10V Universal 120V-277V ELV, TRIAC		
CCT		Alabaster : 2700K Alabaster : 3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

