

CUPOLA ALABASTER 18 LIGHT CHANDELIER

VISUAL COMFORT & Co.

PRODUCT FEATURES



LAMPING

Includes 120V or 277V 77.4 watts, 6192 delivered lumens, 3000K LED module. Dimmable with most LED compatible ELV and TRIAC dimmers. 277V dimmable with 0-10V dimmers. Ships with 9 feet of field-cutttable matte black cord. Can be installed on a sloped ceiling up to 45° when swag hooks are used.

ORDERING INFORMATION

SLCH516	COLOR TEMP	FINISH	VOLTAGE
	30 3000K	HAB HAND RUBBED ANTIQUE BRASS	120V
		B NIGHTSHADE BLACK	-277 277V

SLCH516 _____

JOB NAME _____

NOTES _____



CUPOLA ALABASTER 18 LIGHT CHANDELIER

VISUAL COMFORT & Co.

SPECIFICATIONS

PRIMARY MATERIAL	Aluminum or Brass
SHADE MATERIAL	Alabaster
NET WEIGHT	35.5 lbs
HEIGHT	4.7in
WIDTH	11in
LENGTH	44.6in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
MIN. HANGING HEIGHT	14.6in
MAX HANGING HEIGHT	110.6in
TOTAL CORD LENGTH	108in
TOTAL STEM LENGTH	
STEM QTY	
SLOPED CEILING ADAPTABLE?	N/A
GENERAL LISTING	ETL Listed
INCLUDES	

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		6192		
WATTS		4.3		
MAX WATTAGE PER BULB		77.4W		
		120V ELV, TRIAC 277V 0-10V		
CCT		3000K		
CRI		90 CRI		
LED LIFETIME		>50000		
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

