Featuring an elegant minimal design, the Filo 23 outdoor wall sconce is designed for reduced glare wayfinding with indirect light illuminating softly against the wall paired with a downlight illumination to highlight architectural features. Sized to match architectural scale.

• Universal 120V-227V

· Outstanding protection against the elements:

- Wet Listed IP65 Rated
- Stainless Steel Mounting Hardware
- Powder Coat Finishes

SPECIFICATIONS


DELIVERED LUMENS	1187.5
WATTS	23.89
VOLTAGE	Universal 120V-277V
DIMMING	Dimmable with most LED compatible ELV & TRIAC dimmers + 0-10V
LIGHT DISTRIBUTION	Symmetric
OPTICS	Downlight optic 30°
MOUNTING OPTIONS	Wall
CCT	3000K
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B1-U3-G1
DARK SKY	Non-Compliant
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2019 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	No
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; >60,000 Hours
WARRANTY*	5 Years
WEIGHT	3.5 lbs.

^{*} Visit techlighting.com for specific warranty limitations and details.



ORDERING INFORMATION

PRODUCT	CRI/CCT	LENGTH	FINISH	VOLTAGE
7000WFLO	930 90 CRI 3000K	23 23"	B BLACK Z BRONZE	UNV 120V - 277V




Filo 23 Outdoor Wall

PHOTOMETRICS*

*For latest photometrics, please visit www.techlighting.com/OUTDOOR

FILO 23 OUTDOOR WALL

Total Lumen Output: 1125.0
Total Power: 23.9
Luminaire Efficacy: 47.1
Color Temp: 3000K
CRI: 90
BUG Rating: B1-U3-G1



PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES

TECH LIGHTING

Visual Comfort & Co.

(I)

© 2020 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400