K-Hello

FreeJack	N	1onoRail	Two-Circui MonoRail	Wall MonoRail	_	Kable Lite	T~trak™	_
N/A		N/A	N/A	N/A		-9	N/A	

ARCHITECTURAL HEAD



K-HELLO Shown approximately 70% actual size.

DESCRIPTION

Highly adjustable head tilts between cables and rotates 140° within its ring. Integral louver lens holder can hold a single lens (sold separately) or eggcrate louver (included). Specify low-voltage MR16 lamp with 3.5" or 5.5" cable separation or PAR36 AR111 with 6.5" separation.

SYSTEM

Available for Kable Lite only.

COLOR None.

FINISH

Satin aluminum only.

LAMP


Low-voltage Halogen MR16 lamp up to 50 watts or PAR36 AR111 up to 75 watts (not included).

ACCESSORIES AND OPTICAL CONTROLS

Compatible MR16 optical controls (sold separately): Glass Lens, MR16 Snout.

WEIGHT

0.30 lb./0.14 kg. ±



ORDERING INFORMATION

700KHELLO

TYPE / CABLE SEPARATION (A) 3 MR16 / 3.5"

5 MR16 / 5.5"

6 PAR36 / 6.5"



7400 Linder Avenue Skokie, Illinois 60077

www.techlighting.com

700KHELLO
FIXTURE TYPE:
JOB NAME:

hds_khello_spec.pdf

© 2007 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.

T 847.410.4400

F 847.410.4500