## PRODUCT FEATURES

- From the brand formerly known as Tech Lighting
- Die-cast aluminum structure, powder coat finish, and stainless steel hardware for robust durability in harsh elements. Appropriate for commercial use.
- · Recessed LED to minimize glare
- Up and downlight
- Universal 120-277 volt driver.
- \* The LED Driver is housed within the junction box. (L. 3.03" | W. 1.5" | H. 1.12")

LAMPING

Black



## ORDERING INFORMATION

7000WLYD	CRI	COLOR TEMP	LENGTH (A)	FINISH	VOLTAGE
	9 90 CRI	303000K	20 20"	B BLACK	UNV UNIVERSAL 120V-277V


7000WLYD	
JOB NAME	
NOTES	



# LLOYDS 20 OUTDOOR WALL

## **SPECIFICATIONS**

PRIMARY MATERIAL	Aluminum
SHADE MATERIAL	Aluminum
NET WEIGHT	4.5 lbs
HEIGHT	20in
WIDTH	2.5in
LENGTH	4.8in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP	
DELIVERED LUMENS		640			
WATTS		19.6			
MAX WATTAGE PER BULB					
		Universal 120V-277V 0-10, ELV, TF	RIAC		
ССТ		3000K			
CRI		90 CRI			
LED LIFETIME					
L70		>60000			
AVERAGE BULB HOURS					
FIELD SERVICEABLE LED					
LAMP BASE		Integrated LED			
LAMP SHAPE		Integrated LED			
LAMP INCLUDED?		True			
WARRANTY**		5 Years			

<sup>\*</sup> Dimming information available at <a href="https://www.techlighting.com/Downloads#dimming">www.techlighting.com/Downloads#dimming</a>

## T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with			
California Building Energy Efficiency	Yes		
Standards 2016 Title 24 Part 6 / JA8.			
This product can be used to comply with			
California Appliance Efficiency Standards			
2016 Title 20 and may be shipped to and			
sold in California.			

 $<sup>^{\</sup>star}$  If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



<sup>\*\*</sup> Visit techlighting.com for specific warranty limitations and details.