TECH LIGHTING

PRODUCT FEATURES

- Modern rectilinear light with a crisp clean design
- Enhanced crystalline inner acrylic shade
- Fully dimmable integrated LED lamp
- Complementary Milan Wall Sconce and two additional length sizes also available by Tech Lighting
- Available in two sleek finish options, Satin Nickel and Chrome
- 5 year warranty with LED lamping option, visit techlighting.com for more warranty details



LAMPING

Includes 20 watt, 1629 delivered lumen, 3000K LED module. Dimmable with low-voltage electronic dimmer.



ORDERING INFORMATION

700BCMLN LENGTH (A)	COLOR	FINISH	LAMP	
24 24"	W WHITE GLASS	C CHROME	-LED930 LED 90 CRI 3000K 120V (T24)	
		S SATIN NICKEL	- LED930-277 LED 90 CRI 3000K 277V	


700BCMLN		
JOB NAME	 	
NOTES		



TECH LIGHTING

SPECIFICATIONS

HARDWARE MATERIAL	Metal
SHADE MATERIAL	Glass
NET WEIGHT	4.0 lbs
HEIGHT	5in
WIDTH	2.8in
LENGTH	24.5in
WET LISTED	
DAMP LISTED	Yes
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS		20		
MAX WATTAGE PER BULB		20W		
INPUT VOLTAGE		120V 277V		
DIMMING TYPE*		White Glass : ELV, TRIAC White Glass : 0-10V		
ССТ		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		50000		
AVERAGE BULB HOURS		50000		
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		Υ		
WARRANTY**		5 Years		

^{*} Dimming information available at www.techlighting.com/Downloads#dimming ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

^{*}If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

