
## **ASSEMBLY INSTRUCTIONS**



## Bryant Bath Sconce

Item # TOB2015

WE RECOMMMEND INSTLLATION OF THIS LIGHTING FIXTURE BE DNE BY A LICENSED ELECTRICIAN.

WARNING \*\*\* SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT, DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

- 1. Remove mounting plate (A) from fixture base (D) by removing base screws (C).
- 2. Affix mounting plate (A) to wall outlet box with mounting screws (B) provided.
- Attach ground (green) wire to ground wire from wall outlet box (usually green
  or copper in color), fasten together with a plastic wire connector. Tightly wrap
  the wire connector with electrical tape so the end of the connector is sealed.
  IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE
  PROPERLY GROUNDED.
- 4. Connect neutral (white) fixture wire coming from fixture base to neutral (usually white) outlet wire. Fasten both wires together with a plastic wire connector and tightly wrap the wire connector with electrical tape.
- Repeat the procedure with the hot (black) wires. Always make sure that no wire strands are left outside the connectors.
   DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OTHERWISE SAFETY WILL BE COMPROMISED.
- 6. Attach fixture base (D) to mounting plate (A) and tighten with base screws (C).
- 7. Insert light bulb T (not included) into the socket (E).
- 8. Loosen set screws (F), insert glass shade (G) into glass holder (E), secure by tightening set screws (F).