### **TRIMLESS HOUSING**

#### 4.5" Volta

## **WAC LIGHTING**

### Responsible Lighting®

#### **SPECIFICATIONS**

**Input:** Universal 120 - 277V AC 50/60 Hz

**Standards:** ETL & cETL, Chicago Plenum, IC-rated, Airtight (see below for list)

**Dimming:** Electronic Low Voltage (ELV): 100%-5%

0-10V: 100%-0%

Lutron Hi-Lume 1% Fade-to-Black option

**Emergency:** EM fixtures provided with integral Emergency battery back up with

24" lead wire remote test switch. Provides at least 90 minutes of 5W

illumination during emergency operation.

**Mounting:** New construction housings included with universal mounting

brackets and hanger bars (Min. 14½" & Max. 24½")

Ceiling cut out (Round): Ø 5 1/8" Ceiling cut out (Square): 5 1/8" x 5 1/8" See next page for ceiling thickness information


Construction: 20 Gauge cold rolled steel


Diecast spackle flange included

**Warranty** 5 year WAC Lighting product warranty

#### **Round New Construction**







### Square New Construction


Fixture Type:


Project:

Location:

Catalog Number:







#### **HOUSINGS**

	Model		Power*	S	N, F,W, A	Rating	Driver		Emergency Backup	Compatible Trims
Round New Construction	R4RNL R4RCL	Airtight Airtight, Chicago Plenum	15 25 36	10W 15W 22W	15W 23W 34W	IC rated IC rated Non-IC	DEFAULT L1	ELV, 0-10V Lutron Hi-Lume 1%	EM	R4RD2L R4RD1L R4RAL R4RWL
Square New Construction	R4SNL R4SCL	Airtight Airtight, Chicago Plenum	15 25 36	10W 15W 22W	15W 23W 34W	IC rated IC rated Non-IC	DEFAULT L1	ELV, 0-10V Lutron Hi-Lume 1%	EM	R4SD2L R4SD1L R4SAL R4SWL

<sup>\*</sup>Power consumption depends on beam angle of the trim.

R4 -

(800) 526.2585

Example: R4RNL-15 or R4RNL-15EM (with Emergency backup battery)

waclighting.com	Headquarters/Eastern Distribution Center
Phone (800) 526.2588	44 Harbor Park Drive

Port Washington, NY 11050

**Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

Driver for 15W New Construction Hsg

Driver for 23W New Construction Hsg Driver for 34W New Construction Hsg

Field Replaceable Driver

D-R4N-15

D-R4N-25

D-R4N-36

### TRIMLESS HOUSING

4.5" Volta

# WAC LIGHTING

Responsible Lighting®

#### **CEILING THICKNESS BY TRIM**

		Ceiling Thickness				
Trim Model	Trim Description	1/2"	1"	1 1/2"		
R4RD2L R4SD2L	Downlight	Yes	Yes	Yes		
R4RD1L R4SD1L	Shallow Regressed Downlight	Yes	Yes	Yes		
R4RAL R4SAL	Adjustable	Yes, to 45°	Yes, to 45°	Yes, to 35°		
R4RWL R4SWL Wall Wash		Yes	Yes	No		