## Model: HM1-LED202

## AC LED Track Luminaire

## WAC LIGHTING

Responsible Lighting®

		Fixture Type:
	7"	Catalog Number:
		Project:
	25%" 334"	Location:

#### PRODUCT DESCRIPTION

LED202 track luminaire offers driverless AC LED technology and easy change of beam angles in field. Superior light output in a small, unobtrusive design. The high output LEDs outperform halogen 50W MR16. Developed for upscale residential and commercial environments.

#### FEATURES

- Driverless AC LED technology
- Compact integrated design
- Easy change of beam angles in field
- Outperforms halogen 50W MR16
- Consistent high quality beam pattern
- Accommodates 1 lens accessory
- 360° horizontal and 90° vertical aiming
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

#### SPECIFICATIONS

ORDER NUMBER


Construction:	Die-cast aluminum with removable PC lens cap for easy change of lenses or accessories
Finish:	Platinum (PT).
Driver:	Input voltage: 120VAC 50/60Hz.
Light Source:	High Voltage AC LED module.


Dimming:	Dims to 10%-100% with electronic low voltage (ELV)
	dimmer. Compatible with LUTRON SELV-300P,
	DVELV-300P and LEVITON MLE03-1.

Standards: ETL & cETL Listed. Energy Star Rated.

## BEAMSHIFT™ TECHNOLOGY

LED202 track luminaires come with BeamShift<sup>TM</sup>, allowing in-field change of beam angle simply by changing the location of the lens with a simple flat-head screwdriver.





 Flood 40° Configuration
 Spot 25° Configuration

 Convex Lens located behind the spacer
 Convex Lens located

#### Spot 25° Configuration Convex Lens located in front of the spacer.

FINISHES

Track System	Model	Finish	Voltage	Color Temp	Power	CRI	Beam	Lumens	Efficacy	PT
	150000.00		1201/	2000//	1514/	05	25°	540	36 Lm/W	
HM1 Flexrail1 <sup>™</sup> LED202	LED202-30	D202-30 PT Platinum	120V	3000K	15W	85 -	40°	660	44 Lm/W	
HM1 – L	ED202-3	0 – PT	7			LENSES	& ACCESS	ORIES		
						Model		Color		
								AMB	Amber	
								BLU	Blue	
						LENS-16	Color Le		Blue Green	
						LENS-16	Color Le			

**WAC Lighting** www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. NOV 2014


## AC LED Track Luminaire

# WAC LIGHTING

Responsible Lighting®

### **APPLICATION PERFORMANCE – 3000K**

## PHOTOMETRY





45° Aiming Angle (ceiling to wall)

	LED202-30				LED202-30			
	25° beam				40° beam			
Distance	FC	L	W		FC	L	w	
4 ft	26	3.7	2.5		21	6.7	4.1	
6 ft	12	5.6	3.8	]	9	10.1	6.2	
8 ft	7	7.5	5.0		5	13.4	8.2	
10 ft	4	9.3	6.3	]	3	16.8	10.3	



Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585