


HR2LEDT509P

2" Tesla™ Pro LED Square 0-30° Adjustable

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, square 0° to 30° adjustable trim with interior open reflector.

FEATURES

- 2" aperture
- Energy Star® rated
- CEC Title 24 Compliant (see below for list of models)
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+


Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing


Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. See table below for Energy Star® and 2013 California Title 24 qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	2013 Title 24	Finish
HR2LEDT509P 0°-30° Adjustable	N 30°	827 2700K	85	795	1870	Yes	No	BN Brushed Nickel CB Copper Bronze WT White 
		927 2700K	90	645	1504	Yes	Yes	
		830 3000K	85	820	1895	Yes	No	
		930 3000K	90	740	1801	Yes	Yes	
		835 3500K	85	895	2075	Yes	No	
		840 4000K	85	910	2164	Yes	No	
	F 45°	827 2700K	85	765	1066	Yes	No	
		927 2700K	90	620	876	Yes	No	
		830 3000K	85	800	1099	Yes	No	
		930 3000K	90	705	988	Yes	Yes	
		835 3500K	85	860	1205	Yes	No	
		840 4000K	85	870	1226	Yes	No	

HR2LEDT509P



Example: HR2LEDT509PF835BN

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

REPLACEMENT MODULES

Model	Input	Notes
HR-2LED-H09D-ICA	120V-277V	Ceiling thickness: 1/2" - 3/4"
HR-2LED-H09D-ICAC		
HR-2LED-R09D-A	120V-277V	Does not accommodate adjustments for T309P, T409P, T509P Requires 3" of clearance from insulation on all sides Ceiling thickness: 1/2" - 1"

Reflectors	
Narrow Flood	SL-REF-BL10-1-N
Flood	SL-REF-BL10-1-F

LED	
2700K 85 CRI	BXRC-27E1000-B-03
2700K 90 CRI	BXRC-27G1000-B-03
3000K 85 CRI	BXRC-30E1000-B-03
3000K 90 CRI	BXRC-30G1000-B-03
3500K 85 CRI	BXRC-35E1000-B-03
4000K 85 CRI	BXRC-40E1000-B-03

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760