


# HR3LEDT518P

3.5" Tesla™ Pro LED Square 0-30° Adjustable

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

## PRODUCT DESCRIPTION

Minimum profile, square 0° to 30° adjustable trim with interior open reflector.

## FEATURES

- 3.5" aperture
- Energy Star® rated
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

## SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Light Source:** Utilizes one 22W LED, CRI: 85 & 90+


**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)

**Mounting:** Three heavy gauge retention clips hold trim firmly to housing.

**Finish:** White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

**Standards:** ETL & cETL Listed. See table below for Energy Star® qualifying products.

## TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	Finish
HR3LEDT518P <i>0° to 30° Adjustable</i>	N 30°	<b>827</b> 2700K	85	1135	2469	Yes	<b>BN</b> Brushed Nickel <b>CB</b> Copper Bronze <b>WT</b> White 
		<b>927</b> 2700K	90	950	2092	Yes	
		<b>830</b> 3000K	85	1165	2540	Yes	
		<b>930</b> 3000K	90	1065	2381	Yes	
		<b>835</b> 3500K	85	1270	2791	Yes	
		<b>840</b> 4000K	85	1295	2792	Yes	
	F 52°	<b>827</b> 2700K	85	1100	1358	Yes	
		<b>927</b> 2700K	90	990	1258	Yes	
		<b>830</b> 3000K	85	1140	1435	Yes	
		<b>930</b> 3000K	90	1030	1303	Yes	
		<b>835</b> 3500K	85	1230	1550	Yes	
		<b>840</b> 4000K	85	1265	1580	Yes	

## HR3LEDT518P

Example: HR3LEDT518PF835BN

**COMPATIBLE HOUSINGS** See individual housing spec sheets for complete information.

Model	Input	Notes
<b>HR-3LED-H18D1-ICA</b> <i>New Construction IC-Rated, Airtight</i>	120V -277V	Allows adjustment in one direction when used with adjustable trims  Ceiling thickness: 1/2" - 3/4"
<b>HR-3LED-H18D1-ICAC</b> <i>New Construction IC-Rated, Airtight Chicago Plenum</i>		
<b>HR-3LED-H18D-ICA</b> <i>New Construction IC-Rated, Airtight</i>	120V -277V	Allows adjustment in any direction when used with adjustable trims  Ceiling thickness: 1/2" - 3/4"
<b>HR-3LED-H18D-ICAC</b> <i>New Construction IC-Rated, Airtight Chicago Plenum</i>		
<b>HR-3LED-H18D-EMICA</b> <i>New Construction IC-Rated, Airtight Emergency Backup Battery</i>		

## REPLACEMENT MODULES

### Reflectors

Narrow Flood **SL-REF-BL10-1-N**  
Flood **SL-REF-BL10-1-F**

### LED

2700K	85 CRI	<b>BXRC-27E1000-B-03</b>
2700K	90 CRI	<b>BXRC-27G1000-B-03</b>
3000K	85 CRI	<b>BXRC-30E1000-B-03</b>
3000K	90 CRI	<b>BXRC-30G1000-B-03</b>
3500K	85 CRI	<b>BXRC-35E1000-B-03</b>
4000K	85 CRI	<b>BXRC-40E1000-B-03</b>

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760