


# HR3LEDT918P

3.5" Tesla™ Pro LED 30°-45° Adjustable Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

## PRODUCT DESCRIPTION

Minimum profile, square 30° to 45° adjustable trim with interior open reflector.

## FEATURES

- 3.5" aperture
- Energy Star® rated (see below for list of models)
- Damp location listed
- 30° visual cutoff angle for glare control
- Ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

## SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Light Source:** Utilizes one 22W LED, CRI: 85 & 90+


**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)

**Mounting:** Three heavy gauge retention clips hold trim firmly to housing.

**Finish:** White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

**Standards:** ETL & cETL Listed. See table below for Energy Star® qualifying products.

## TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	Finish
HR3LEDT918P 30°-45° Adjustable	N 26°	827 2700K	85	1000	2537	Yes	<b>BN</b> Brushed Nickel <b>CB</b> Copper Bronze <b>WT</b> White 
		927 2700K	90	845	2177	No	
		830 3000K	85	1045	2665	Yes	
		930 3000K	90	950	2460	Yes	
		835 3500K	85	1135	2933	Yes	
		840 4000K	85	1150	2916	Yes	
	F 38°	827 2700K	85	955	1569	Yes	
		927 2700K	90	825	1351	No	
		830 3000K	85	1015	1662	Yes	
		930 3000K	90	925	1509	Yes	
		835 3500K	85	1090	1509	Yes	
		840 4000K	85	1115	1834	Yes	

## HR3LEDT918P

Example: HR3LEDT918PF835CB

**COMPATIBLE HOUSINGS** See individual housing spec sheets for complete information.

Model	Input	Notes
HR-3LED-H18D1-ICA	120V-277V	Allows adjustment in one direction when used with adjustable trims Ceiling thickness: 1/2" - 3/4"
HR-3LED-H18D1-ICAC		
HR-3LED-H18D-ICA	120V-277V	Allows adjustment in any direction when used with adjustable trims Ceiling thickness: 1/2" - 3/4"
HR-3LED-H18D-ICAC		
HR-3LED-H18D-EMICA		

## REPLACEMENT MODULES

### Reflectors

Narrow Flood **SL-REF-BL10-1-N**  
Flood **SL-REF-BL10-1-F**

### LED

2700K	85 CRI	<b>BXRC-27E1000-B-03</b>
2700K	90 CRI	<b>BXRC-27G1000-B-03</b>
3000K	85 CRI	<b>BXRC-30E1000-B-03</b>
3000K	90 CRI	<b>BXRC-30G1000-B-03</b>
3500K	85 CRI	<b>BXRC-35E1000-B-03</b>
4000K	85 CRI	<b>BXRC-40E1000-B-03</b>

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760