# R2RD2T, R2SD2T

# 2" Volta - Downlight Trim

# **WAC LIGHTING**

## Responsible Lighting®



## PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

#### **FEATURES**

- 1" regressed lens for superior glare control
- · Integral patterned tempered trim lens included standard
- Compatible with a wide range of accessories
- 5 year WAC Lighting product warranty

#### **SPECIFICATIONS**

Construction: Durable die-cast self-flanged aluminum construction

Input: Universal 120 - 277V AC 50/60 Hz

**Dimming:** Electronic Low Voltage (ELV): 100%-5% (120V only)

0-10V: 100%-0% (120 - 277V)

**Light Source:** High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard.

Ceiling cut out Round Trimmed: Ø 3 %6" Invisible Trim: Ø 4 ¼"

Ceiling cut out Square Trimmed: 3 %6" x 3 %6" Invisible Trim: 4 %1" x 4 %1"

Accomodates 1/2 "- 1 1/2" ceiling thickness

**Finish:** Electrostatically powder coated White, Black. Enamel coated Haze.

Plated and brushed Copper Bronze.

Standards: ETL & cETL Wet location Listed

CRCD

				Lumens	CDCP				
Model	Ве	eam		Referenc	e Output*	Color Temp	CRI	Finishes	Reflector/Trim
		<b>c</b> 1:	Round	390	5515	<b>827</b> 2700k			Black Black/White Copper Bronze Haze Haze/White White
	;	<b>S</b> 12	Square	405	5405		)K 85	BK BKWT CB HZ HZWT WT	
			Round	1260	6030	<b>830</b> <i>300</i> 0	K 85		
5½"		N 25		1375	5505	<b>835</b> <i>350</i> (	3500K 85		
	d Trim		Square	1373		<b>840</b> 4000	K 85		
1" <b>R2SD2T</b> Squa	re Trim	<b>-</b> 4/	Round	1305	3355				
2½" -    1	F W	<b>F</b> 40°	Square	1390	3110	927 2700K 930 3000K	N 00		
<del>-315/16"</del>			Round	830	1175				
		<b>W</b> 60	Square	985	1115		/N 90		

R2\_\_D2T-\_\_\_-

Example: R2SD2T-N840-WT

\*Reference output shows 830(85CRI 3000K) trim with 22 housing. Use multiplier table below to determine the output for other combinations.

Multiplier		TRIM						
Multipi	lier	827	927	830	930	835	840	
HOUSING	22	0.95	0.81	1.00	0.86	1.05	1.07	
HOUSING	15	0.66	0.56	0.69	0.59	0.72	0.74	

Example: R2SD2T-N840-WT with 15 housing: 1375 lm (Reference Output) x 0.74 (Multiplier) = 1018 lm

5505 CBCP (Reference Output) x 0.74 (Multiplier) = 4074 CBCP

Please see next page for housing units(required)


waclighting.comHeadquarters/Eastern Distribution CenterCentral Distribution CenterWestern Distribution CenterPhone (800) 526.258844 Harbor Park Drive1600 Distribution Ct1750 Archibald AvenueFax(800) 526.2585Port Washington, NY 11050Lithia Springs, GA 30122Ontario, CA 91760

# R2RD2T, R2SD2T

# WAC LIGHTING

# 2" Volta - Downlight Trim

## Responsible Lighting®



**R2**\_\_\_\_-Example: **R2RNT-15** or

R2RNT-15EM (with Emergency backup battery)

WOOD AND METAL CEILING ADAPTERS

R2R-ADP1 ½" to 1" ceiling thickness

R2R-ADP2 1" to 1½" ceiling thickness

R2S-ADP1 ½"to 1"ceiling thickness

R2S-ADP2 1" to 1½"ceiling thickness



## **ACCESSORY HOLDER** sold separately

LENS-16-HLD Required for use with any lens or accessory

## INTERCHANGEABLE REFLECTORS

REF-R2-N Narrow Flood beam
REF-R2-F Flood beam
REF-R2-W Wide beam

## **LENS ACCESSORIES**

	AMB	Amber			
	RED	Red			
LENS-16	FR	Frosted			
	SPR	Spread			
	BEL	Beam Elongating			

## **GLARE CONTROL ACCESSORIES**

LENS-16	нсм	Honeycomb Louver
	CRL	Cross Louver

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760