

3.5" OCULUX ARCHITECTURAL

Adjustable Downlight - R3CRDT, R3CRDL

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Oculux Architectural offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

FEATURES

- 3 beam angle options included:
Narrow flood beam film pre-installed, interchangeable flood beam film supplied, remove film for spot beam.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing:
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Shallow housing under 4" depth
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast aluminum trim and heat sink

Dimming: 100% - 1% TRIAC, ELV
100% - 5%, 0-10V

Input Power: 13.5W, 120V-277V 50/60Hz

Light Source: High output COB LED rated life of 50,000 hours.

Mounting: Retention clips firmly hold trim to housing. Cutout 4¼"

Finish: Powder coated white, enamel-coated haze.

Ceiling thickness: ½" - 1"

Standards: UL & cUL, Wet location listed. Energy Star® 2.0
Title 24 JA8-2016 Compliant

Operating Temperature: -4°F to 104°F (-20°C to 40°C)

Trims (Order Housing Separately)

	Model	Beam	Color Temp	Lumens	CBCP	Finish
<p>R3CRDT Round Trim Downlight & Adjustable</p>	Spot 16°	927 2700K	855 4989	HZWT Haze/White WT White		
		930 3000K	920 5364			
		935 3500K	935 5472			
		940 4000K	980 5740			
	Narrow Flood 36°	927 2700K	840 1463			
		930 3000K	905 1574			
		935 3500K	920 1605			
		940 4000K	965 1683			
	Flood 51°	927 2700K	805 839			
		930 3000K	865 902			
		935 3500K	885 920			
		940 4000K	925 965			
<p>R3CRDL Round Trimless Downlight & Adjustable</p>	Spot 16°	927 2700K	855 4989	HZ Haze WT White		
		930 3000K	920 5364			
		935 3500K	935 5472			
		940 4000K	980 5740			
	Narrow Flood 36°	927 2700K	840 1463			
		930 3000K	905 1574			
		935 3500K	920 1605			
		940 4000K	965 1683			
	Flood 51°	927 2700K	805 839			
		930 3000K	865 902			
		935 3500K	885 920			
		940 4000K	925 965			

R3CRD _ - _

Example: R3CRDT-WT

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760

3.5" OCULUX ARCHITECTURAL Adjustable Downlight - R3CRDT, R3CRDL


WAC LIGHTING
Responsible Lighting®

Housings (Required) - Order separately from trims

Model

Color Temp

Input



R3CRN-11
IC-Rated, Airtight
New Construction

927	2700K	120V - 277V
930	3000K	
935	3500K	
940	4000K	

Example: **R3CRN-11-927**

FEATURES

- Adjustable LED light engine included with housing:
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

GLARE CONTROL ACCESSORIES sold separately

LENS-16	HCL	Honeycomb Louver
----------------	------------	------------------

LENS ACCESSORIES sold separately

LENS-16	AMB	Amber
	RED	Red
	FR	Frosted
	SPR	Spread
	BEL	Beam Elongating

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760