
Model: WL-LED100


LEDme® Step Light


WAC LIGHTING

Responsible Lighting®









Fixture Type:	
Catalog Number:	
Project·	

PRODUCT DESCRIPTION

Horizontal rectangle LEDme® Step Light. Designed for safety and style on stairways, patios, decks, balcony areas, walkways and building perimeters. Features an architectural design. Energy efficient for long-lasting indoor and outdoor lighting solutions. Creates an attractive, romantic impression at night.

FEATURES

- 316 marine grade cast stainless steel (SS) available
- · Direct wiring, no driver needed
- Low profile, flush to wall aesthetics with no visible hardware
- Turtle friendly (AM, RD colors)
- · 40,000 hour rated life
- Balanced lighting, free of shadows with minimum glare

l m

45

- Up to 200 fixtures can be connected in parallel
- Replaceable LED module
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum or 316 marine grade cast stainless steel

Power: Direct wiring, no remote driver needed. Input voltage: 120V or 277V AC 50/60Hz

Light Source: 3000K CCT Samsung HV-AC High Power LED, CRI: 85 Optional color lenses. Total power consumption of 3.9W

Mounting: Fits into $2'' \times 4''$ J-Box with minimum inside dimensions of $3''L \times 2''W \times 2''H$

Includes bracket for J-Box mount. See next page for spacing recommendations

Dimming: Dim to 10% with electronic low voltage (ELV) dimmer Approved dimmers: Lutron Skylark SELV-300P-WH and Leviton Vizia VPE04

Standards: IP66, UL & cUL Listed for wet locations

Model #

Lm

Location:

FIXTURE PERFORMANCE

WL-LED100-C-SS

Model#

WL-LED100-AM-SS	28
WL-LED100-RD-SS	3
WL-LED100-BL-SS	5
WL-LED100F-C-SS	37
WL-LED100F-AM-SS	20
WL-LED100F-RD-SS	2
WL-LED100F-BL-SS	4

WL-LED100-C-BK	31
WL-LED100-AM-BK	19
WL-LED100-RD-BK	2
WL-LED100-BL-BK	3
WL-LED100F-C-BK	25
WL-LED100F-AM-BK	14
WL-LED100F-RD-BK	1.5

WL-LED100F-BL-BK

Lm

Model#

WL-LED100-C-WT

WI-I FD100-AM-WT

Model#

WE EED IOO AIM WI	50
WL-LED100-RD-WT	4
WL-LED100-BL-WT	8
WL-LED100F-C-WT	58
WL-LED100F-AM-WT	29
WL-LED100F-RD-WT	3
WL-LED100F-BL-WT	6

68	WL-LED100-C-BN	31
38	WL-LED100-AM-BN	19
4	WL-LED100-RD-BN	2
8	WL-LED100-BL-BN	3
58	WL-LED100F-C-BN	25
29	WL-LED100F-AM-BN	14

WL-LED100F-RD-BN

WL-LED100F-BL-BN

WL-LED100-C-BZ	32
WL-LED100-AM-BZ	21
WL-LED100-RD-BZ	2
WL-LED100-BL-BZ	4
WL-LED100F-C-BZ	27

l m

Model #


Lm

WL-LED100F-C-BZ	27
WL-LED100F-AM-BZ	15
WL-LED100F-RD-BZ	2
WL-LED100F-BL-BZ	3

ORDER NUMBER

Model #		Color		Finish		
WL-LED100 WL-LED100F		C AM RD BL	White Amber Red Blue	3000K 610nm 640nm 450nm	SS BK WT BN BZ	Stainless Steel Black White Brushed Nickel Bronze

FINISHES




Example: WL-LED100F-BL-SS


WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

Spacing Recommendations for Optimal Light Distribution


Corridors / Hallways



Stairs - Wall Mount



Stairs - Step Mount



Mount in center of stair as close to the upper tread as possible. For best results use one light per step for steps narrower than 5'.