TUBE - model: WS-W2609, WS-W2610 LED Wall Mount

Example: WS-W2609-WT

(800) 526.2585

waclighting.com

Fax

Phone (800) 526.2588



Responsible Lighting®

	Fixture Type:
	Catalog Number:
	Project:
	Location:
PRODUCT DESCRIPTION	SPECIFICATIONS
A curved contemporary look with impactful style. Perfect for illuminating the parameter of a home or creating a safe entryway to a building, the modern, minimalist TUBE wall mount features a crescent profile. Crafted of aluminum with etched glass, this LED luminaire is offered in five handsome finishes and two energy efficient LED configurations. Mounts upward or downward to suit nearly any exterior design scheme. FEATURES	Construction: Aluminum with etched glass. Power: Integral driver in luminaire. 120V - 277V input. Light Source: High output LED Mounting: Mounts directly to junction box Dimming: 0-10V Dimming: 100%-10% ELV Dimming: 100%-15% (120V only) Finish: Brushed Aluminum (AL), Black (BK), Bronze (BZ), Graphite (GH), White (WT)
 Energy Star® rated CEC Title 24 Compliant IP65 Rated, ETL & cETL Wet Location Listed Mounts up or down Die-Cast Aluminum Construction Universal Voltage Input (120V - 277V) Dimming: ELV (120V) or 0-10V ADA Compliant 	 Color Temp: 3000K CRI: 90 Rated Life: 70,000 hours Standards: Energy Star® rated, IP65 Rated, ETL & cETL Wet Location Listed, CEC Title 24 Compliant, Dark Sky Friendly. ometry Voltage Watt Lumens Finish
Single Light 10", 376", WS-W2609 Single Light 5%" Energy Star®	120V-277V 16W 825
$Double Light = \frac{10^{"}}{10^{"}} + \frac{376^{"}}{10^{"}} + \frac{376^{"}}{10^$	AL Brushed Aluminum BK Black BZ Bronze GH Graphite WT White

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 2015

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050