

1500 Cherokee Parkway, Suite 100, Acworth, GA 30102

Phone: (866) 845-5451 • Fax: (866) 816-6165

Email: service@acclaim-lighting.com • www.acclaim-lighting.com

IN10050 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

Assembly method 1:

- 1. Screw the Loop (18) to the Fixture Nipple (17).
- 2. Secure the Top Loop (15) to the Canopy (11) with Washer (13) and Nut (14).
- 3. Attach Chain (16) onto the Loop (18) and Top Loop (15). Close Chain (16) with chain pliers (not provided)


3.Install bulbs: (bulbs not included)


Assembly method 2:


- 1. Secure the Canopy (11) to the Fixture Nipple (17) with Washer (13) and Nut (14).
- 2. Install bulbs: (bulbs not included)

Electrical installation

- 1. Thread two machine screws (8) through the mounting bar (9) and secure with the hex nut (7).
- 2. Secure the mounting bar (9) with mounting screw (10) to the outlet box (1).
- 3. Pull out the outlet wire and ground wire from the outlet box (1). Make wire connections.
- --Ribbed /white wire (w/o marking) from light to White wire (2) from power source.
- --Smooth/black wire (w/o marking) from light to Black wire (3) from power source.
- --Loop the ground wire (4) to mounting bar (9) with a ground screw (6).
- 4. Attach the fixture canopy (11) to the outlet box (1), secure with the ball nut (12).







- 1. OUTLET BOX
- 2. WHITE WIRE
- 3. BLACK WIRE
- 4. GROUND WIRE
- 5. WIRE CONNECTOR
- 6. GROUND SCREW
- 7. HEX NUT
- 8. MACHINE SCREW
- 9. MOUNTING BAR
- 10. MOUNTING SCREW

- 11. CANOPY
- 12 BALL NUT
- 13. WASHER
- 14. NUT
- 15. TOP LOOP
- 16. CHAIN
- 17. FIXTURE NIPPLE
- 18. LOOP