# IN20002 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

### **CAUTION**

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

## **GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

# ASSEMBLY AND INSTALLATION

- 1. Thread the rod (20) into the coupling (21), then place the tube (19), cap (18) to the rod (20) and secure with the nut (17).
- 2. Connect stems (14)(15)(16), then screw them into the rod (20) and the swivel (13).
- 3. Thread two machine screws (6) to the mounting plate (7) and secure with the hex nut (9).
- 4. Secure the mounting plate (7) to the outlet box (1) with mounting screws (10).
- 5. Pull out the outlet wire and ground wire from the outlet box (1). Make wire connections.
- --Ribbed wire (w/o marking) from light to White wire (2) from power source.
- --Smooth wire (w/o marking) from light to Black wire (4) from power source.
- --Loop the ground wire (3) to mounting plate (7) with a ground screw (8).
- 6. Attach the canopy (11) against the outlet box (1), secure with the ball nut (12).
- 7. Attach the glass shade (24) to the socket cap (22), then secure with the knob (23).
- 8. Install bulbs: (bulbs not included)

(Do not exceed the maximum capacity recommended on the sockets).

### INSTALLATION IS NOW COMPLETE

