

1500 Cherokee Parkway, Suite 100, Acworth, GA 30102

Phone: (866) 845-5451 • Fax: (866) 816-6165

E: service@acclaim-lighting.com • www.acclaim-lighting.com

IN41230 / IN41235 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors. Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

- 1. Carefully unpack and lay out the parts as shown in illustration and read all instructions before starting.
- 2. Attach nipple (10) to cross bar (7), and then secure it with a hex nut (9).
- 3. Attach the cross bar (7) to outlet box (1) by using two box screws (8).
- 4. Connect Supply Wire with Fixture Wire using wire Nut Connectors (5).
- -Ribbed wire (w/o marking) from light to White wire (2) from power source
- -Smooth wire (w/o marking) from light to Black wire (3) from power source
- -Loop the ground wire (4) to cross bar (7) with a ground screw (6)
- -Tuck all wires into Outlet Box (1).
- 5. Attach fixture to cross bar (7) by inserting the nipple (10), and then secure it with nut (11).
- 6. Attach the glass shade (13) to socket (14), secure them with socket ring (12).
- 7. Screw the bulb (not included) into the socket (14).

