

SW BRELLA



VANITIES WALL

location:

SPECIFICATIONS:

DESCRIPTION

2-4 light vanity luminaires featuring handcrafted glass. Multilight version of 1SW Brella sconce.

LAMPING

Standard: 40W Low-pressure G9 Halogen 120V lamp, included. Suitable for use in an open fixture. Dimmable with standard incandescent

LED: 5W LED Replaceable source 120V, dimmable, included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 6.0" Dia. x 4.0" H, spaced 7.875" apart on center.

CONSTRUCTION

Fixture utilizes metal arm assembly and stamped steel body, with plated finish. Decorative finials can be removed for downlighting applications. Decorative outlet box cover optional when not required.

METAL FINISH

Fixture shall be finished in Bronze, Chrome or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal outlet box, with 1.75" left or right offset. Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



BRELLA SHOWN IN MARBLE (467952)



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14




SW BRELLA

VANITIES WALL


ORDERING:


FIXTURE		- GLASS OPTIONS		- METAL FINISH		- METAL FINISH -		- 0	OPTIONS	
	2SW 2 Light Vanity	467907	White	(blank)	40W G9 Hal	BR	Bronze	SC	Q Square	
	3SW 3 Light Vanity	467952	Marble	LED	5W LED 120V,	CR	Chrome		Canopy	
	4SW 4 Light Vanity	467983	Mocha		dimmable	SN	Satin Nickel			
		4679CH	Cherry							
		4679KR	Chalk							
		46790K	0ak							
		46790P	Bicolor Orange/Pina							
		4679SL	Solare							
		4679TN	Titan							



Ex. 3SW-467983-SN

Brella 3-Light Vanity w/ Mocha Glass, Satin Nickel Finish





LED SCONCES:

- Total power of only 5 watts
- Dimmable with a standard dimmer
- Rated life: 25,000 hours
- 450 lumens
- CCT: 3000° Kelvin
- CRI: 80+

 4SW: 3	0.375" L	
	T	Tr.

Canopy allows direct wiring without outlet box, where armored cable or non-metallic sheathed cable is employed, and the decorative outlet box cover is not required. Orient upward or downward, wall-mount only.

Project Info	ormation:
--------------	-----------