



PIVOT

12V MINI PENDANTS

location:
DRY

SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with handcrafted glass.

LAMPING

LED: 6W Integrated source, dimmable, 85+ CRI, 2800°K CCT, 450 lumens, 30,000 hours.

DIFFUSER

Shade shall be made of handcrafted glass in various decors. 3.25" Dia. x 1.5" H

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish.

STANDARD PENDANT


Mini pendant comes complete with flat-style canopy.

METAL FINISH

Glass retainer hardware and canopies are finished in Satin Nickel.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



PIVOT SHOWN IN OPAL GLOSSY/SMOKE (PIVOTSM)

PIVOTAM
OPAL GLOSSY/AMBER



PIVOTCL
OPAL GLOSSY/CLEAR



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/15



PIVOT

12V MINI PENDANTS


ORDERING:

CONNECTION	-	GLASS OPTIONS	-	LAMP OPTIONS	-	METAL FINISH
Pendant Fixtures		PIVOTAM Opal Glossy/Amber		LED 6W LED		SN Satin Nickel
1XT Flat Canopy		PIVOTCL Opal Glossy/Clear				
		PIVOTSM Opal Glossy/Smoke				

Ex. 1XT-PIVOTAM-LED-SN
Pivot LED Pendant, Opal Glossy/Amber Glass,
Satin Nickel Finish

FIXED PENDANT OPTIONS:

1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic dimmable LED driver, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Satin Nickel metal finish

12V LED MINI PENDANT:

- LED driver is located in canopy for optimal performance
- Total power of 6 watts
- 450 lumens
- Rated life: 30,000 hours
- CCT: 2800° Kelvin
- CRI: 85+
- Dimmable (ELV dimming is recommended)
- Consult factory for 0-10V dimming option.

Project Information: