




## ASSEMBLY INSTRUCTION MODEL #ARC-1917-GA-CL-MWP





All electrical components must be

installed by a licensed electrician

in accordance with the National

Electric Code and the appropriate

local electrical codes.





You will need 9 Candelabra Base Bulb 40 Watts Recommended 60 Watts Max. USE LED BULBS FOR EXTENDED USE

This fixture is Dry rated.

#### **How to Install**

- Do a complete inventory of all parts and components before you start installing.
- 2. Assemble one end of chain to fixture loop by opening quick link.

Fasten mounting hardware to junction box with machine screws.

After wires are connected, turn screw collar loop onto nipple, then place canopy up against ceiling and lock by screw collar loop ring.

- **3.** After safely attaching fixture into junction box ,install bulbs and proceed to connecting the power.
- **4.** When you begin to dress the fixture, start with package labeled(A).
- 5. IMPORTANT: Apply crystal sets in alphabetical order.


#### **Crystal Sets**

- A. 36sets 27\*14mm
- B. 54sets 47\*14mm
- C. 1set 2\*14mm+1\*76mm drop
- D. 1set 3\*14mm+1\*76mm drop
- E. 1set 4\*14mm+1\*76mm drop
- F. 1set 5\*14mm+1\*76mm drop
- G. 1set 6\*14mm+1\*76mm drop
- H. 1set 7\*14mm+1\*76mm drop





### PART NUMBER MODEL #ARC-1917-GA-CL-MWP



# Part Number

#### Part Numbers

- A. (1)-Mounting Hardware
- B. (1)-Canopy;ø5\*H1" (XBN1917GACAN5IN)
- C. (1)-Screw Collar Loop Ring
- D. (1)-Screw Collar Loop
- E. (1)-Chain;L72" (XBN1905GACHA4MM)
- F. (1)-Fixture Loop;ø2"
- G. (1)-Upper Ring;ø6 3/4"
- H. (1)-Lower Ring;ø6 1/4"
- I. (1)-Center Stem;L18 1/2" J. (1)-Bottom Ring;ø24 "
- K. (1)-Bottom Finial;H1 1/5" (XBN1917GAFIN)