


Revolve

Our Recessed family has grown with a new range of adjustable downlights. The effortless design and high functionality of these fixtures are sure to make a welcome addition in any room.



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
GBR35-CC	3.5"	12 W	800 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
GBR06-CC	6"	20 W	1500 lm			

Specifications

Every fixture includes a junction box with an integrated driver
 Over 50,000 hours service life
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K
 40° beam angle
 30° tilting, 360° rotation
 Cast aluminum construction
 Suitable for wet locations
 Compatible with TRIAC and ELV dimmers
 Refer to website for dimmer compatibility
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 5-year warranty

Finish

○ **WH** White

Accessories

RFP-UNI (GBR06)
 Universal rough-in plate

RFP-35 (GBR35)
 Rough-in plate

RFP-46 (GBR06)
 Rough-in plate

Order example

GBR06-CC-WH

Dimmable 6" deep regressed gimbal in a white finish

Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

