

# Facet

This versatile modern thin-trim 2-, 4- and 6-inch gimbal with multi-directional adjustable swivel produces a bright glow with minimal glare as a result of its regressed light source. Ideal for general lighting or for areas requiring a directional light to showcase unique elements or to create dramatic wall-wash effects.

**UPGRADE**

WET    LOW-GLARE    SWIVEL/DIRECTIONAL 30°    ETL US Intertek    IC RATED

AIR TIGHT    2700k 3000k 3500k 4000k 5000k    COLOR TEMPERATURE



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>RGM2-CC</b>	2"	8 W	660 lm	800 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
<b>RGM4-CC</b>	4"	12 W	1050 lm	1400 lm	90		120 V
<b>RGM6-CC</b>	6"	20 W	1370 lm	1800 lm	90		120 V

### Specifications

Every fixture includes a junction box with integrated dimmable driver  
 Can be daisy chained  
 Superior LED performance and lifespan  
 Regressed light source  
 Minimal heat emission  
 Aluminum construction  
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 40° beam angle  
 30° tilting, 360° rotation  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 Ideal operating temperature:  
 -20° to 40° C  
 5-year warranty

### Finish

- **BK** Black
- **WH** White

### Accessories

- RFP-UNI**  
Universal rough-in plate
- RFP-23**  
Rough-in plate for 2" model
- RFP-46**  
Rough-in plate for 4" and 6" models

### Order example

**RGM4-CC-BK**  
 4" gimbal recessed downlight with 1050 Lumens at 3000 K in a black finish

### Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

