WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Mini Pendant 4CCT

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
O PD-69424 24"	 2700K 3000K 3500K 4000K 	O BK Black	8 W	655	291

Example: PD-69424-40-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wisp of light. This sleek and refined pendant is tipped with an acrylic diffuser, casting diffused illumination while emphasizing its minimalistic style.

FEATURES

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Spin-on round canopy with minimal hardware
- Driver installed within the Junction Box, driver dimension: 2.8" x 1.3" x 1.1"

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K	
Input:	120-277V,50/60Hz	
CRI	90	
Dimming:	ELV: 100-10% , 0-10V: 100-5% , TRIAC: 100-5%	
Rated Life:	50,000 Hours	
Standards:	ndards: ETL, cETL, Damp Location Listed	
Construction	Aluminum body with etched acrylic diffuser	

FINISHES:



REPLACEMENT PARTS RPL-GLA-69424 - Acrylic Diffuser

LINE DRAWING:

