

WAC LIGHTING

Cyllindra

Linear Multi Light 4CCT

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-77503L	2700K/3000K/3500K/4000K	AB Aged Brass BC Black Chrome	28W	2299	1642

Example: **PD-77503L-BC**

For custom requests please contact customs@wacighting.com

DESCRIPTION

A translucent glass sphere divided by a single metallic band captures a clean, modern aesthetic. Multiple pendants are installed on a square canopy to make a impressive visual statement in any space.

FEATURES

- Thin, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with acrylic globes

Fixture Type:


Catalog Number:

Project:


Location:



FINISHES:



LINE DRAWING:



WAC LIGHTING

Cyllindra

Linear Multi Light 4CCT

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-77505L	2700K/3000K/3500K/4000K	AB Aged Brass BC Black Chrome	48W	3941	2815

Example: **PD-77505L-BC**

For custom requests please contact customs@wacighting.com

DESCRIPTION

A translucent glass sphere divided by a single metallic band captures a clean, modern aesthetic. Multiple pendants are installed on a square canopy to make a impressive visual statement in any space.

FEATURES

- Thin, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with acrylic globes

Fixture Type: _____


Catalog Number: _____

Project: _____


Location: _____



FINISHES:



LINE DRAWING:



WAC LIGHTING

Cyllindra

Linear Multi Light 4CCT

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-77514L	2700K/3000K/3500K/ 4000K	AB Aged Brass BC Black Chrome	132W	10296	7354

Example: **PD-77514L-BC**

For custom requests please contact customs@wacighting.com

DESCRIPTION

A translucent glass sphere divided by a single metallic band captures a clean, modern aesthetic. Multiple pendants are installed on a square canopy to make a impressive visual statement in any space.

FEATURES

- Thin, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with acrylic globes

Fixture Type: _____


Catalog Number: _____

Project: _____


Location: _____



FINISHES:



LINE DRAWING:



WAC LIGHTING

Cyllindra

Linear Multi Light 4CCT

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-77523L	2700K/3000K/3500K/4000K	AB Aged Brass BC Black Chrome	236W	15961	11401

Example: **PD-77523L-BC**

For custom requests please contact customs@wacighting.com

DESCRIPTION

A translucent glass sphere divided by a single metallic band captures a clean, modern aesthetic. Multiple pendants are installed on a square canopy to make a impressive visual statement in any space.

FEATURES


- Thin, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Driver included
- 5 Year warranty

SPECIFICATIONS


Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with acrylic globes



FINISHES:



LINE DRAWING:



PD-77523L