LINK – model: WS-106 dwelLEDTM LED Sconce

WAC LIGHTING

Responsible Lighting®

	Fixture Type:
	Catalog Number:
	Project:
14" 2½"	Location:

PRODUCT DESCRIPTION

Lovely as a single sconce or when installed in multiples as an interconnected display. Link features a silk screened glass diffuser with a ceramic white glaze, and looks great mounted vertically or horizontaly. Constructed with a solid die cast aluminum and a handsome brushed nickel finish.

FEATURES

- Silk-screened glass diffuser with a white ceramic glaze
- · Mount vertically or horizontally
- Conversion plate for 4" junction box included
- Driver located in a standard 2" x 4" junction box
- Universal driver (120V-220V-277V)
- Color Temp: 3000K
- CRI: 90

Dimming: 100% - 10% ELVRated Life: 38,000 hoursInput: 120 - 277V

SPECIFICATIONS

Construction: Aluminum and White Silk Screened Glass

Light Source: High output LED.

Finish: Brushed Nickel (BN)

Standards: ETL & cETL damp location listed.

ORDER NUMBER

	Watt	LED Lumens	Delivered Lumens	Finish		
WS-10614	20.5W	985	380	BN	Brushed Nickel	

Example: WS-10614-BN