

WAC LIGHTING

Portos

Wall Sconce 4CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS118618 18"	2700K/3000K/3500K/4000K	AB Aged Brass	15W	674	572

Example: **WS118618-AB**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Portos recalls the grace of early modern design, reimagined for today. Light glimmers through the fluted glass surface, radiating warmth and sophistication. Portos adds structure and softness in equal measure, an elegant expression of craftsmanship.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Driver concealed within the canopy
- Available in black finish for indoor/outdoor(WS-W118618-BK)
- Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum body with ribbed glass diffuser




FINISHES:



Aged Brass

LINE DRAWING



WS&WSW118618

WAC LIGHTING

Portos

Wall Sconce 4CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS118625 25"	2700K/3000K/3500K/4000K	AB Aged Brass	20W	1131	961

Example: **WS118625-AB**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Portos recalls the grace of early modern design, reimagined for today. Light glimmers through the fluted glass surface, radiating warmth and sophistication. Portos adds structure and softness in equal measure, an elegant expression of craftsmanship.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Driver concealed within the canopy
- Available in black finish for indoor/outdoor(WS-W118618-BK)
- Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum body with ribbed glass diffuser



FINISHES:



Aged Brass

LINE DRAWING

