

Spectacle

Bath & Wall 4CCT

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-71524 24"	2700K	AB Aged Brass BN Brushed Nickel	17W	700	357
	3000K				
	3500K				
	4000K				

Example: WS-71524-40-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

Cool Shades. Two illuminated ovals on a rectangular backplate create a unique design for the Bath + Wall Light.

FEATURES

- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- \bullet Decorative conversion plate to accommodate standard 4" junction box is included
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp: 2700K,3000K,3500K,4000K

Input: 120-277V,50/60Hz

CRI 90

Dimming: ELV: 100-10%, 0-10V: 100-10%, TRIAC: 100-10%

Rated Life: 50,000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed

Construction Aluminum hardware with silicone diffuser

REPLACEMENT PARTS

RPL-CON18-BN - CONVERSION PLATE FOR WS-71524/




FINISHES:





Brushed

LINE DRAWING:



WS-7152

WAC LIGHTING

Spectacle

Bath & Wall 4CCT

Fixture Type:		
Catalog Number:		
Project:		
Location:		

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-71534 34"	2700K	AB Aged Brass BN Brushed Nickel	21W	900	546
	3000K				
	3500K				
	4000K				

Example: WS-71534-40-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

Cool Shades. Two illuminated ovals on a rectangular backplate create a unique design for the Bath + Wall Light.

FEATURES

- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- \bullet Decorative conversion plate to accommodate standard 4" junction box is included
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp: 2700K,3000K,3500K,4000K

Input: 120-277V,50/60Hz

CRI 90

Dimming: ELV: 100-10%, 0-10V: 100-10%, TRIAC: 100-10%

Rated Life: 50,000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed

Construction Aluminum hardware with silicone diffuser

REPLACEMENT PARTS

RPL-CON18-BN - CONVERSION PLATE FOR WS-71524/



FINISHES:





Aged Brass Brushed

LINE DRAWING:

