# WAC LIGHTING Ripple

# Bath & Wall 4CCT

Fixture Type:

Catalog Number:

Project: Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens	
WS-85524 24"	2700K	AB Aged Brass BN Brushed Nickel	15W	422 449	363 374	
	3000K					
	3500K					
	4000K					

## Example: WS-85524-40-BN

For custom requests please contact customs@waclighting.com

## DESCRIPTION

A glimmering bar of textured glass makes a luminous impression. Its sleek square metal wall plate anchors a cylindrical metal collar holding the lightbar in place.

### FEATURES

• Built in color temperature adjustability. Switch from

- 2700K/3000K/3500K/4000K
- · Option to pre-select color temperature or adjust in the field
- ACLED driverless technology
- 5 Year warranty


### SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware with glass diffuser

### FINISHES:



## LINE DRAWING:



WS-85524



# WAC LIGHTING Ripple

# Bath & Wall 4CCT

Fixture Type:

Catalog Number: Project:

Location:

	1001				
Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-85532 32"	2700K	AB Aged Brass	19W	545	467
		BN Brushed Nickel		562	481
	3000K				
	25001/				
	3500K				
	4000K				

## Example: WS-85532-40-BN

For custom requests please contact customs@waclighting.com

## DESCRIPTION

A glimmering bar of textured glass makes a luminous impression. Its sleek square metal wall plate anchors a cylindrical metal collar holding the lightbar in place.

### FEATURES

• Built in color temperature adjustability. Switch from

- 2700K/3000K/3500K/4000K
- · Option to pre-select color temperature or adjust in the field
- ACLED driverless technology
- 5 Year warranty

### SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware with glass diffuser

#### FINISHES:



# LINE DRAWING:

