

WAC LIGHTING

Beech

Outdoor Wall Sconce 4CCT

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W89516 16"	2700K	BK Black	20W	1700	587
	3000K				
	3500K				
	4000K				

Example: **WS-W89516-40-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

A slab of bark-textured glass gives an organic feel to this otherwise sleek silhouette. Patterned illumination spills from its ruffled surface.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Light engine is factory sealed for maximum protection from the elements
- Weather resistant powder coated finish
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	54,000 Hours
Standards:	ETL, cETL, IP65, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum hardware




FINISHES:



Black

LINE DRAWING:



WS-W89516

WAC LIGHTING

Beech

Outdoor Wall Sconce 4CCT

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W89524 24"	2700K	BK Black	29W	2517	912
	3000K				
	3500K				
	4000K				

Example: **WS-W89524-40-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

A slab of bark-textured glass gives an organic feel to this otherwise sleek silhouette. Patterned illumination spills from its ruffled surface.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Light engine is factory sealed for maximum protection from the elements
- Weather resistant powder coated finish
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	54,000 Hours
Standards:	ETL, cETL, IP65, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum hardware




FINISHES:



Black

LINE DRAWING:



WS-W89524