

Installation manual for: V1800SR36

Dimensions: D36" H86" L32

Collection:Spiral

Bulb Type:E12 bulb not included

Lamp Frame Weight (1bs):54.6

Total Weight(lbs):105



Thank you for choosing our product(s).

Our Company is actively involved in every step of the production.

Our product(s) are designed to be utilized for every application that graces your home or business.

We pride ourselves in providing the most prompt and courtesy service to all of the valued customers.

Please find the enclosed detailed instruction and read carefully for proper installation.

If you have any questions, please contact the retailer where the purchased was made.



SAFETY

Warning: MAKE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF. BY EITHER REMOVING THE FUSE OR TURNING OFF THE CIRCUIT BREAKER.


CAUTION

- Before assembling the lighting fixture, please read all instructions carefully.
- All frame & crystal components are fragile, please handle with care.
- Required supply circuit: 110 130V/60Hz
- Labeled wires are "L" for live wire, "N" for neutral wire, "E" for ground wire.
- Never install fixture on damp ceiling, the room should be dry and well ventilated
- All electrical components must be installed by a licensed electrician and in accordance with the National Electrical Code and the appropriate local electrical codes.

Unpack the Package

Please open the box carefully and check all the items are inside the box. If you have any installation, assembling and missing parts questions, where you purchase from and any other relevant information ready, our customer service team will provide comprehensive and worry free service to our valued customers.

Frame Parts List



V1800SR36 D36" H86" L32

Step 1

Please use the parts list to ensure you are not missing any parts

V1800SR36

PARTS LIST

part	picture	Description	Parts Number	Qty	Check list
part	preture	Description	rarts Number	Qty	Check fist
ZA		4"Mounting bracket		1	
ZB		6"Canopy cover	CP10R60L3	1	
ZC		Canopy ring		1	
ZD		L59"Chain06T Twist Design	CHAIN06T	1	
ZE	~~	Power Cord 12' SPT-2-16# Clear/Gold		1	
P1	• •	Loop		1	
P2		4.8"Iron bracket		3	
Р3		3.2"Iron bracket		3	
P4		9"Metal ring		1	
P5		Lamp body(1)		1	
Р6		3.5"Metal wire box		1	


V1800SR36 D36" H86" L32

part	picture	Description	Parts Number	Qty	Check list
P7		Hickey		3	
P8		3.5"Metal plate		1	
Р9	0	Coupling		5	
P10		16"Both end Threaded pipe		1	
P11		15″Iron bracket		8	
P12		Lamp body(2)		1	
P13		Steel wire		1	
P14		6.3"Metal wire box		1	
P15		6.3"Metal plate		1	
P16	0	1.7"Iron bracket		1	
P17		22.3"Both end Threaded pipe		1	
P18		6.3"Metal wire box		1	
P19		6.3"Metal plate		1	

(03

part	picture	Description	Parts Number	Qty	Check list
P20	<u></u>	25.8"Both end Threaded pipe		1	
P21	MMM	Metal strip		1	
P22		E12 Lampholder		32	
В		1050-14#*3pcs		56	
С	-∞ ∞ () ∞ ∞	1050-14#*18pcs		44	
Е	- 	1050-14#*16pcs		158	
F		1050-14#*16pcs		405	
	-	(05)	-		

part	picture	Description	Parts Number	Qty	Check list



IMPORTANT: Test sockets with bulb before dressing the fixture.

- 1 .Drill a ϕ 0.7" hole in the ceiling reinforcment to allow a $\frac{11}{16}$ " threaded rod to pass through.
- 2 .Attach the electrical box to the ceiling reinforcment and pass the $^{11}\!/_{16}$ threaded rod through the box and secure it to the heavy duty hickey.
- 3 . Pass the fixture wires and ground wire through the loop, canopy ring, center hole of canopy and the heavy duty hickey.
- 4. Pull ceiling wires down through the fixture box and make connection.
- 5 . Screw loop only onto threaded pipe.
- 6 . Hang the fixture on chain.
- 7 . Secure the canopy with canopy ring.

"L" = Hot wire

"N" = Neutral wire


"E" = Ground wire

(07)

V1800SR36 D36" H86" L32

Step 3

Frame Assembly Diagram



Frame Assembly Instructions

Installation:

Please read all instructions carefully. Before you proceed to install, make sure. that the power supply is turned off and remains off until installation is complete. Please note that each part has been assigned a number. Please proceed in a numerical order.

- 1. Hang the chain (01) on the ceiling.
- 2. Fix the plated cylinder screw connector (05), cylinder screws (06) and cylinder screw connector (07) together in the lamp body.
- 3. Screw the threaded pipe (03) on the lamp body (04).
- 4. Screw the lamp body (02) on the threaded pipe (03).
- 5. Connect the all lamp on the chain (01) bottom ring.
- 6. Pull up the steel wire through the lamp body arrive the Mounting bracket the fix it.
- 7. Connect the lamp main wire with positive and negative of 4"J-box are correct.
- 8. As the crystal dressing instruction, hang the crystal parts. NOTE: The fixture have the steel wire, you can't cut it, please use the steel wire and pull up it to the canopy to fix the fixture.


The end!

Step 4 Crystal Dressing Instructions

1. Hang crystal "B" "C" "E" "F".

Crystal Dressing Diagram

When dressing the chandelier with the crystals please remember to wear either rubber or cotton gloves. So as to prevent any damage or smudging on the crystals.



Congratulations!

You are now done installing your Elegant Lighting fixture. Sit back and admire each crystal as it will become the statement piece for your room/house.

Thank you.

Cleaning and Maintenance of Chandelier Frame
The finish on our chandelier frames and fixture
frames is protected by a durable coating of
lacquer. To clean, use a clean soft, dry cloth. Do
not use any metal polishes, cleaners, abrasives
or any substance which could remove the
protective finish. Failure to follow these
instructions automatically voids the guarantee.

Cleaning and Maintenance of Crystals Wet a soft cotton fabric in clean warm water and wipe gently, then polish with a dry soft cotton fabric.

To Order Crystal Replacement Parts
Should you require replacement crystals or pins
(the metal connectors attaching the crystals),
contact the store where the product was
purchased. For ease of ordering, you may use the
original crystal trimming instructions provided
with this product and circle the items you wish
to order, indicating the quantity by writing the
number needed adjacent to the circle. You will
be contacted with prices prior to shipment. All
orders must be pre-paid.

Elegant Lighting Warranty

The finish and frame of your new chandelier or fixture are warranted for a period of one (1) year from the date of purchase. Our company will, at its option, repair or replace any frame that has a defect in the materials or workmanship during the warranty period. All crystals are guaranteed for their original quality during the life of the chandelier. Breakage is not covered by this warranty.

To make a claim under this warranty, contact our customer service department. A written return authorization form will be sent to you with specific instructions.

Returns and Conditions of Warranty

Returns must be pre-authorized by contacting the retailer where you made your purchase.. Returns will only be accepted with a written return merchandise authorization and return shipping charges pre-paid. We reseserve the right to inspect all returned merchandise to fully determine the nature of any defect. This guarantee shall not apply to any product that has been changed, altered or otherwise modified, nor shall it apply to any product that has been repaired or altered by anyone other than a pre-authorized facility. We will not be responsible for any breakage or damages incurred during transit, nor for crystal parts or metal frame part that have been subject to misuse, negligence, accident or inappropriate handling. Also, we will not be held responsible for damage incurred during improper installation or wiring by others, nor for damages resulting from a failure to follow the recommended maintenance or installation procedures. This guarantee is issued in lieu of any and all other guaranteed or warrantee, whether written or implied and any and all other obligations or liabilities. Further, we neither authorize nor permit any other person or firm to assume for us, any liability in connection with the sale of our products.