


# ASSEMBLY INSTRUCTION MODEL #ED0451002CH





All electrical components must be installed by a licensed electrician in accordance with the National Electric Code and the appropriate local electrical codes.



You will need 2-Candelabra Base Bulb 40 Watts recommended 60 Watts Max. USE LED BULBS FOR EXTENDED USE

The fixture is Dry rated

### **HOW TO INSTALL:**

Place the fixture parts on a soft cloth-covered platform before installation of fixture.

- 1. Install the mounting bar onto the outlet box.
- Raise the Frame up over the threaded nipple on the mounting bar.
  After the wire connection is completed, Secure with the coupling.
- 3. Screw the center stem onto the coupling and secure with the nut.
- Adjust the hex nut along the bottom end of the center stem to allow the vase cap to stay in the correct position.
  Secure the cap with the finial.
- 5. Dress the crystals as illustrated.



# ASSEMBLY INSTRUCTION MODEL #ED0451002CH

# **Part Number**

### Part Numbers

- A. (2)-Wire Connector
- B. (1)-Mounting bar
- C. (2)-Screw
- D. (1)-Hex nut
- E. (1)-Threaded nipple
- F. (1)-Frame; Ø10"; 25 pin holes; with inner plate.
- G. (1)-Coupling
- H. (2)-Hex Nut
- I. (2)-Socket
- J. (1)-Center stem ; H 4 1/2"-XSN708CHSTEM4.5IN
- K. (1)-Vase Cap ; Ø3" ; 25 pin holes-XSN710CHCAP3IN
- L. (1)-Finial-XSN710CHFIN

